

PUBLIC NOTICE
LOUISIANA DEPARTMENT OF ENVIRONMENTAL QUALITY (LDEQ)
MINOR SOURCE AIR GENERAL PERMIT
PROPOSED GENERAL PERMIT FOR SURFACE COATING AND FABRICATION

The LDEQ, Office of Environmental Services, is accepting written comments on the generic template for the Minor Source Surface Coating and Fabrication Operating Permits. The General Permit can be issued for an Initial, Modification or Renewal for any company, located in the State of Louisiana for the qualifying facility. **The facility is located in any Parish.**

The draft General Permit Facility Specific Requirements section contains the universe of regulations that may apply to the facility and associated equipment. The General Permit Briefing Sheet and associated Specific Requirements is the generic template for all General permits to be issued by the Department. On a site specific basis, this generic template will be modified to describe the facility process and list only those regulations that apply to the facility requesting this General Permit.

The public is invited to comment on the list of regulations and the language of each specific requirement which will be available for use in issuing General Permits. This general permit incorporates several new regulations. A listing of the regulations added at this time can be found in the Preamble to the Statement of Basis.

1. The permitting authority may issue a general permit intended to cover numerous similar sources or activities. General permits shall be issued in accordance with LAC 33:III.519 and, prior to issuance, shall undergo public notice. Each general permit shall incorporate terms and conditions applicable to sources that would qualify for the general permit. Any general permit shall identify criteria by which sources may qualify for the general permit, and may provide for applications which deviate from the requirements of LAC 33:III.517.
2. The owner or operator of any source which would qualify for the general permit may apply for authorization to operate under the general permit. The application must include all information necessary to determine qualification for and to assure compliance with the general permit.
3. The permitting authority may approve an owner or operator's application for authorization to operate under the general permit without repeating the public participation procedures. Such an approval shall not be a final permit action for purposes of judicial review regarding the terms and conditions of the general permit.

The draft General Permit Facility Specific Requirements section contains the universe of regulations that may apply to the facility and associated equipment. If any regulation applies to any facility or associated emission source, and is not part of the attached specific conditions, then that facility cannot be granted a General Permit. An exception to this is when there is a specific condition that meets all of the requirements of being a state only requirement. This excludes federally enforceable specific conditions or limitations. The General Permit Statement of Basis provides additional information regarding how a facility specific General Permit contains only those regulations that apply to the specific facility and its associated emission sources.

A technical review of the working draft of the proposed permit was submitted to the facility Louisiana Chemical Association (LCA), Louisiana Mid-Continent Oil and Gas Association (LMOGA), Kean Miller, Shaw Environmental and Infrastructure, and the LDEQ Surveillance Division. Any remarks received during the technical review will be addressed in the "Worksheet for Technical Review of Working Draft of Proposed Permit". All remarks received by LDEQ are included in the record that is available for public review.

Written comments, written requests for a public hearing or written requests for notification of the final decision regarding this permit action may be submitted to Ms. Soumaya Ghosn at LDEQ, Public Participation Group, P.O. Box 4313, Baton Rouge, LA 70821-4313. **Written comments and/or written requests must be received by 12:30 p.m., Tuesday, November 10, 2009.** Written comments will be considered prior to a final permit decision.

If LDEQ finds a significant degree of public interest, a public hearing will be held. LDEQ will send notification of the final permit decision to the applicant and to each person who has submitted written comments or a written request for notification of the final decision.

The draft General Permit Briefing Sheet, General Information Report, Inventories Report, Facility Specific Requirements, and Statement of Basis are available for review at the LDEQ, Public Records Center, Room 127, 602 North 5th Street, Baton Rouge, LA. Viewing hours are from 8:00 a.m. to 4:30 p.m., Monday through Friday (except holidays). **The available information can also be accessed electronically on the Electronic Document Management System (EDMS) on the DEQ public website at www.deq.louisiana.gov.**

Additional copies may be reviewed at the Parish Library Headquarters in each parish of the state. The material can also be viewed at the Calcasieu Parish Library, Sulphur Regional Branch, 1160 Cypress Street, Sulphur, LA 70663-5111 and the Morgan City Public Library, 220 Everett Street, Morgan City, LA 70380.

Inquiries or requests for additional information regarding this permit action should be directed to Lance Green, LDEQ, Air Permits Division, P.O. Box 4313, Baton Rouge, LA 70821-4313, phone (225) 219-3063.

Persons wishing to be included on the LDEQ permit public notice mailing list or for other public participation related questions should contact the Public Participation Group in writing at LDEQ, P.O. Box 4313, Baton Rouge, LA 70821-4313, by email at deqmaillistrequest@la.gov or contact the LDEQ Customer Service Center at (225) 219-LDEQ (219-5337).

Permit public notices including electronic access to the proposed permit and statement of basis can be viewed at the LDEQ permits public notice webpage at www.deq.louisiana.gov/apps/pubNotice/default.asp and general information related to the public participation in permitting activities can be viewed at www.deq.louisiana.gov/portal/tabid/2198/Default.aspx.

Alternatively, individuals may elect to receive the permit public notices via email by subscribing to the LDEQ permits public notice List Server at http://www.doa.louisiana.gov/oes/listservpage/ldeq_pn_listserv.htm.

All correspondence should specify AI Number 163497, Permit Number Minor Source Air General Permit Surface Coating and Fabrication, and Activity Number PER20090001.

Scheduled Publication Date: October 5, 2009

Worksheet for Technical Review of Working Draft of Proposed Permit

Company Name:	Minor Source Air General Permit	AI #:	163497	TEMPO Activity No:	PER200900001
Facility Name:	Surface Coating and Fabrication	Remarks	James McKeivier – LDDEQ SWRO	Submitted by:	
Permit Writer:	Lance Green	Permit Writer	Lance.Green@la.gov	Email address:	

Instructions

Permit Reference – Indicate specific portion(s) of the permit to which the remark relates (i.e. “Specific Condition 120”, or “Section II Air Permit Briefing Sheet”, etc.).

Remarks – Explain the basis for each remark. Provide regulatory citations where possible. If the remark is made due to an error or omission in the permit application this must be noted and the revised information **must be submitted**. Revised information may be submitted separately from this worksheet. Please be aware that revised information must be submitted in writing and certified by the Responsible Official, and if necessary, by a Professional Engineer licensed in Louisiana. *Please Note:* New or additional equipment, processes or operating conditions not addressed in the original permit application will be addressed on a case-by-case basis. The Department reserves the right to address such changes in a separate permit action.

DEQ Response – DO NOT COMPLETE THIS SECTION. This section will be completed by Air Permits Division of DEQ, included in the proposed permit package and made available for public review during the public comment period.

- Additional rows may be added as necessary.
 - Completed Form shall be emailed to the Permit writer in MS Word compatible format within the deadline specified in the email notification.

Permit Reference	Remarks	Air Permits Division Response (for official use only)
General Conditions	LAC 33:III.537 does not exist in the reg. book dated 12/31/08	The General Conditions are available in the amended regulations dated 4/20/2009 under LAC 33:III.537.



OFFICE OF ENVIRONMENTAL SERVICES

PROPOSED Minor Source Air General Permit

Surface Coating and Fabrication

AGENCY INTEREST NO. 163497

ACTIVITY NO. PER20090001

In accordance with the Louisiana Environmental Quality Act, as amended (La. R.S. 30:2001, *et seq.*: "The Act") and the rules and regulations effective or promulgated under the authority of the Act (LAC 33:III.501 and LAC 33:III.513), this Air General Permit is issued. This permit authorizes persons who meet the requirements set forth herein and have been approved by this Office to construct and operate surface coating and fabrication facilities in accordance with the emissions limitations, monitoring requirements, and other conditions of this permit.

This permit shall become effective on

This permit and the authorization to emit shall expire ten (10) years from the effective date of the permit.

Issued on

Cheryl Sonnier Nolan
Assistant Secretary

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

I. STATEMENT OF AUTHORITY – LAC 33:III.513.A

The permitting authority may issue a general permit intended to cover numerous similar sources or activities. General permits shall be issued in accordance with LAC 33:III.519 and, prior to issuance, shall undergo public notice. Each general permit shall incorporate terms and conditions applicable to sources that would qualify for the general permit. Any general permit shall identify criteria by which sources may qualify for the general permit, and may provide for applications which deviate from the requirements of LAC 33:III.517.

The owner or operator of any source that would qualify for the general permit may apply for authorization to operate under the general permit. The application must include all information necessary to determine qualification for and to assure compliance with the general permit.

The permitting authority may approve an owner or operator's application for authorization to operate under the general permit without repeating the public participation procedures. Such an approval shall not be a final permit action for purposes of judicial review regarding the terms and conditions of the general permit.

Any source which is issued the general permit shall, notwithstanding a permit shield, be subject to enforcement action for operation without a permit if the source is later determined not to qualify for the general permit.

II. ELIGIBILITY

This minor source air general permit authorizes construction, operation, and modification of surface coating and fabrication facilities that meet the eligibility requirements outlined herein.

Facilities eligible for coverage under this general permit include facilities primarily engaged in surface coating and fabrication. These facilities are typically classified under Standard Industrial Classification (SIC) Codes beginning with 34xx, 35xx, 36xx, or 37xx.

Facilities which are subject to any 40 CFR 60 New Source Performance Standard or any 40 CFR 63 National Emission Standard for Hazardous Air Pollutants (NESHAP) not specified in this permit are not eligible for coverage. Facilities which strip paint using chloromethane (MeCl) are not eligible for coverage.

Facilities must maintain eligibility to operate under this permit. This permit does **not** authorize operations that are not compliant with the established eligibility conditions. Prior to initiating any modification to the facility that would prohibit it from being covered under this general permit, the permittee must request an "individual" site-specific air permit. If a modification rendering the facility ineligible for this general permit is effected without a site-specific permit in place, the modification will be deemed unauthorized from the date construction commenced and subject to enforcement action.

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

Facilities Excluded from Coverage

This general permit cannot be used to authorize emissions at:

1. "Part 70 Sources" as defined in LAC 33:III.502.
2. Except as described in LAC 33:III.501.B.3.a-b, facilities subject to regulatory requirements not addressed by this general permit, including those with equipment or processes not compliant with Section IV – Equipment-Specific Limitations and Required Controls.
3. Facilities subject to LAC 33:III.Chapter 59—Chemical Accident Prevention or 40 CFR Part 68—Chemical Accident Prevention Provisions.
4. Facilities that formerly operated as major sources if Best Available Control Technology (BACT) or Lowest Achievable Emission Rate (LAER) controls were installed and are being maintained on an existing emissions unit.

III. FACILITY-WIDE EMISSIONS LIMITATIONS

Baton Rouge Nonattainment Area

For facilities located in the parishes of Ascension, East Baton Rouge, Iberville, Livingston, and West Baton Rouge, potential emissions of criteria pollutants and toxic air pollutants (TAP) from the facility (or grouping of contiguous facilities) must be less than the following amounts, in tons per year:

<u>Pollutant</u>	<u>Emissions</u>
PM ₁₀	15
SO ₂	40
NO _X	20
CO	90
Total VOC	20
Total TAPs	20
Any Individual TAP*	Table 1

Other Parishes

Except for facilities located in the parishes of Ascension, East Baton Rouge, Iberville, Livingston, and West Baton Rouge, potential emissions of criteria pollutants and toxic air pollutants (TAP) from the facility (or grouping of contiguous facilities) must be less than the following amounts, in tons per year:

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

<u>Pollutant</u>	<u>Emissions</u>
PM ₁₀	15
SO ₂	40
NO _X	90
CO	90
Total VOC	90
Total TAPs	20
Any Individual TAP*	Table 1

The above limitations shall include emissions from *all* sources at the facility, including emissions from all insignificant activities set forth under LAC 33:III.501.B.5 and those from activities traditionally classified under General Condition XVII (e.g., sampling).

* Any individual Toxic Air Pollutant (TAP) emitted shall not exceed the listed lb/hr and tons/yr limits of Table 1. Facilities which emit a TAP not listed in Table 1 shall not exceed the minimum emission rate (MER) for that TAP listed in Table 51.1 and 51.2 of LAC 33:III.Chapter 51. No individual TAP shall exceed 8 tons per year.

Table 1

LAC 33:III.Chapter 51 Toxic Air Pollutant	Limit lb/hr (8-hour average)	Limit tpy
Acetaldehyde		6.48
Acrolein	0.006	0.013
Antimony (and compounds)	0.013	0.02
Arsenic (and compounds)		0.013
Barium (and compounds)	0.013	0.02
Benzene		1.71
Beryllium(and compounds)		0.013
Biphenyl	0.02	0.05
n-Butyl alcohol	4.04	5.50
Cadmium (and compounds)		0.013
Chromium VI (and compounds)		0.013
Copper (and compounds)	0.026	0.013
Cresol	0.26	0.80
Cumene	6.55	8.00
Dibutyl phthalate	0.13	0.19
1,4-Dichlorobenzene	1.59	8.00
Ethyl benzene	11.51	8.00
Ethylene glycol	2.66	3.32
Formaldehyde		1.10
Glycol ethers	0.63	0.79
n-Hexane	4.68	7.50
Manganese (and compounds)		0.04

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

Table 1 Continued

LAC 33:III Chapter 51 Toxic Air Pollutant	Limit lb/hr (8-hour average)	Limit tpy
Methanol	6.97	8.00
Methyl ethyl ketone	15.65	8.00
Methyl isobutyl ketone	5.45	7.50
Naphthalene (and Methylnaphthalenes)	1.33	1.66
Nickel (and compounds)		0.04
Phenol	0.50	0.70
Polynuclear aromatic hydrocarbons		0.013
Selenium (and compounds)	0.005	0.013
Styrene	5.66	7.06
Toluene	9.95	8.00
Toluene-2,4-diisocyanate	0.0009	0.013
Toluene-2,6-diisocyanate	0.0009	0.013
Xylene (mixed isomers)	11.51	8.00
Zinc (and compounds)	0.13	0.16

IV. EQUIPMENT-SPECIFIC LIMITATIONS AND REQUIRED CONTROLS

A. Internal Combustion Engines (ICEs)

Definitions

Stationary internal combustion engine - any internal combustion engine (ICE), except combustion turbines, that converts heat energy into mechanical work and is not mobile. Stationary ICE differ from mobile ICE in that a stationary internal combustion engine is not a nonroad engine as defined at 40 CFR 1068.30 (excluding paragraph (2)(ii) of that definition), and is not used to propel a motor vehicle or a vehicle used solely for competition. Stationary ICE include reciprocating ICE, rotary ICE, and other ICE, except combustion turbines.

Limitations

ICEs must be fueled by diesel (or fuel oil no. 2). Stationary engines fueled by gasoline, natural gas, or liquefied petroleum gas (LPG) are not eligible for coverage under this permit.

B. Storage Vessels

Gasoline and storage vessels containing volatile organic compounds shall have a capacity less than 10,000 gallons. Storage vessels greater than 250 gallons storing any volatile organic compound having a maximum true vapor pressure of 1.5 psia or greater shall be equipped with a submerged fill pipe.

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

C. Surface Coating

Definitions

Metal Fabrication and Finishing HAP – means cadmium, chromium, lead, manganese, or nickel.

Limitations

Facilities located in the parishes of Ascension, Calcasieu, East Baton Rouge, Iberville, Livingston, Pointe Coupee, and West Baton Rouge which are engaged in the surface coating of Marine Vessels and Oilfield Tubulars and Ancillary Oilfield Equipment may not exceed 3.5 pounds VOC per gallon of coating as applied (minus water and exempt solvent) per LAC 33:III.2123.C.11.b.

V. EMISSIONS INVENTORY

Notwithstanding the applicability provisions of LAC 33:III.919.A, the owner or operator shall submit an annual emissions inventory as described in LAC 33:III.919.B by the date specified in LAC 33:III.919.D (unless an alternate date is specified by LDEQ) if the facility is located in one of the following parishes:

Ascension	East Baton Rouge	Iberville	Livingston
West Baton Rouge	Assumption	East Feliciana	Iberia
Pointe Coupee	St. Helena	St. James	St. John the Baptist
St. Martin	Tangipahoa	West Feliciana	

Notwithstanding the applicability provisions of LAC 33:III.919.A, beginning with the 2010 Emissions Inventory due March 31, 2011, the owner or operator shall submit an annual emissions inventory as described in LAC 33:III.919.B by the date specified in LAC 33:III.919.D (unless an alternate date is specified by LDEQ) if the facility is located in any parish that is designated as a nonattainment area subsequent to the issuance of this general permit or any parish that adjoins such nonattainment parish.

VI. LABORATORY ANALYSES

Laboratory procedures and analyses performed by commercial laboratories shall be conducted in accordance with the requirements set forth under the Laboratory Accreditation procedures established by LAC 33:I.Chapters 45-59. LDEQ will not accept data generated by commercial laboratories that are not accredited under this program, and retesting will be required by an accredited laboratory. Information on the Environmental Laboratory Accreditation Program and a list of labs that have applied for accreditation is available on the LDEQ's website at <http://www.deq.louisiana.gov/portal/tabid/2412/Default.aspx>.

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

VII. MODIFYING A FACILITY

Except as specified below, before effecting any modification to a facility authorized to operate under this general surface coating and fabrication permit (generally commencement of construction) the permittee shall submit a completed Application for Approval of Emissions of Air Pollutants from Minor Sources to the Air Permits Division. Upon submittal of the completed application, the permittee may proceed with the proposed modification. The application forms and instructions are available on the LDEQ's website at <http://www.deq.louisiana.gov/portal/tabcid/2758/Default.aspx>.

Like Kind Replacement of Equipment

Like kind replacement of equipment does not require notification to the Department, provided the:

1. replacement unit is identical to the replaced emissions unit (i.e., the same make and model);
2. replaced emissions unit is permanently removed from the facility or otherwise permanently disabled;
3. potential to emit of the facility does not increase; and
4. replacement unit is not subject to federal or state requirements not applicable to the replaced emissions unit.

Records of such modifications shall be retained on site and made available for inspection by the Office of Environmental Compliance, Surveillance Division for a minimum of five (5) years.

VIII. REQUESTING TERMINATION OF COVERAGE UNDER THIS PERMIT

Permittee shall notify the Air Permits Division using the Application for Approval of Miscellaneous Permitting Actions if operations at the facility permanently cease during the permit term. The application form and instructions are available on the LDEQ's website at <http://www.deq.louisiana.gov/portal/tabcid/2758/Default.aspx>.

IX. NAME/OWNER/OPERATOR CHANGES

The permittee shall notify the Office of Environmental Services in accordance with LAC 33:I Chapter 19 using the Facility Name Change and Change of Ownership Form (NOC-1). The form and instructions are available on the LDEQ's website at <http://www.deq.louisiana.gov/portal/tabcid/65/Default.aspx>.

X. RENEWAL OF COVERAGE UNDER THE GENERAL PERMIT

A permit application to renew coverage under the permit shall be submitted thirty (30) days prior to, but no earlier than 12 months before, the expiration date of the general permit. The application procedures shall be the same as those outlined in Section VII,

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

except that a fee shall not be required unless the renewal application is also associated with a modification. If the owner or operator fails to submit a timely and complete renewal application, the owner's or operator's right to operate the source will terminate upon the expiration date of the general permit.

XI. GENERAL COVERAGE

Continuation of an Expired General Permit

If this permit is not reissued or replaced prior to the expiration date, it will be administratively continued and remain in force and effect. Provided a timely renewal application has been submitted in accordance with section X of this general permit, any permittee who was granted permit coverage prior to the expiration date will automatically remain covered by the continued permit until the earlier of:

1. reissuance or replacement of this permit, at which time the permittee must comply with the conditions of the new permit to maintain authorization to operate; or
2. termination of the permit; or
3. issuance of a site-specific permit to the facility; or
4. a formal permit decision by LDEQ not to reissue this general permit, at which time the permittee must seek coverage under a site-specific permit.

Requirement for a Site-Specific Permit

Eligibility for this permit does not confer a vested right to coverage under the permit. LDEQ may require any person authorized by this permit to apply for and/or obtain a site-specific air permit. If LDEQ requires a permittee authorized to emit under this permit to apply for a site-specific air permit, LDEQ will notify the permittee in writing that a permit application is required. This notification will include a brief statement of the reasons for this decision, a statement setting a deadline for the permittee to file the application, and a statement that on the effective date of issuance or denial of the site-specific air permit, coverage under this permit will automatically terminate. LDEQ may grant additional time to submit the application upon request of the applicant. If a permittee fails to submit in a timely manner a site-specific air permit application as required by LDEQ, then the applicability of this permit to the individual permittee will be automatically terminated at the end of the day specified by LDEQ for application submittal.

LDEQ's notification that coverage under a site-specific permit is required does not imply that the facility does not meet the eligibility requirements of this permit.

Severability

The provisions of this permit are severable and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

application of such provision to other circumstances and the remainder of this permit shall not be affected thereby.

XII. REOPENER CLAUSE

This permit may be modified, revoked and reissued, or terminated for cause. Upon modification or reissuance of this permit, the permittee shall comply with any new or modified requirements by any compliance dates established in the modified or reissued permit.

Please be advised that pursuant to provisions of the Environmental Quality Act and the Administrative Procedure Act, the Department may initiate review of a permit during its term. However, before it takes any action to modify, suspend or revoke a permit, the Department shall, in accordance with applicable statutes and regulations, notify the permittee by mail of the facts or operational conduct that warrant the intended action and provide the permittee with the opportunity to demonstrate compliance with all lawful requirements for the retention of the effective permit.

If there is evidence indicating that the air emissions authorized by this permit cause or have the reasonable potential to cause or contribute to a violation of a NAAQS, the facility may be required to obtain a site-specific permit or this permit may be modified to include different limitations and/or requirements.

XIII. PUBLIC NOTICE

Request for public comment on this Minor Source Air General Permit for Surface Coating and Fabrication was published in *The Louisiana Register* on <Month> 20, 2009; and in *The Advocate*, Baton Rouge; *The Times-Picayune*, New Orleans; *The News-Star*, Monroe; *The Lake Charles American Press*, Lake Charles; *The Times of Shreveport*, Shreveport; *The Advertiser*, Lafayette; the *Town Talk of Alexandria*, Alexandria; and in *The Courier of Houma*, Houma on <date>, 2009. All comments will be considered prior to a final permit decision.

As specified in LAC 33:III.513.A.3, the permitting authority may approve an owner or operator's application for authorization to operate under the general permit without repeating the public participation procedures.

XIV. GENERAL CONDITIONS

The following general conditions from LAC 33:III.537 apply, except as modified below.

MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001

SURFACE COATING AND FABRICATION

General Condition	Applicable	Comments
I.	Yes.	Facility-wide emissions limitations are set forth in Section III of this general permit.
II.	Yes.	
III.	Yes.	This permit does not contain sections entitled "Emission Rates for Criteria Pollutants" and "Emission Rates for TAP/HAP and Other Pollutants." If emissions from an emissions unit are subsequently determined to be greater than those disclosed in a permit application, but facility-wide emissions remain within the limits set forth in Section III of this general permit, the owner or operator shall submit a revised application in accordance with Section VII of this general permit as soon as practicable, but no later than 30 days after discovery of the discrepancy. In such situations, the owner or operator is not required to submit a report pursuant to General Condition XI unless an underlying federal or state standard has been violated. If a facility-wide emission limitation has been exceeded, a report must be submitted pursuant to General Condition XI.
IV.	Yes.	
V.	No.	
VI.	Yes.	
VII.	Yes.	
VIII.	No.	Testing and reporting deadlines are established by the Specific Requirements of this permit.
IX.	No.	See Section VII of this general permit and General Condition III.
X.	Yes.	
XI.	Yes.	See comment associated with General Condition III.
XII.	Yes.	
XIII.	Yes.	
XIV.	Yes.	
XV.	No.	
XVI.	Yes.	See Section IX of this general permit.
XVII.	Yes.	Only General Condition XVII activities disclosed in the permit application are considered authorized discharges.
XVIII.	See comment.	General Condition XVIII applies to the master general permit itself, but does extend to the action of granting coverage under this general permit. According to LAC 33:III.513.A.3, LDEQ may "approve an owner or operator's application for authorization to operate under the general permit without repeating the public participation procedures. Such an approval shall not be a final permit action for purposes of judicial review regarding the terms and conditions of the general permit."
XIX.	No.	
XX.	Yes.	

**MINOR SOURCE AIR GENERAL PERMIT
AGENCY INTEREST NO. 163497
ACTIVITY NO. PER20090001**

SURFACE COATING AND FABRICATION

In addition, the following additional general conditions apply:

- XXI. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- XXII. No person shall falsify, tamper with, or knowingly render inaccurate, any monitoring device or method required to be maintained under this permit.
- XXIII. The permittee must take all reasonable steps to minimize or prevent any emissions in violation of this permit which have a reasonable likelihood of adversely affecting human health or the environment. The permittee shall also take all reasonable steps to minimize or correct any adverse impact on the environment resulting from noncompliance with the permit, including accelerated or additional monitoring as necessary to determine the nature and impact of the noncomplying emissions.
- XXIV. The permittee shall furnish to the Department, within a reasonable time to be specified by the Department, any information which the Department may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this standard permit. The permittee shall also furnish to the Department, upon request, copies of records required to be kept by this permit.
- XXV. Nothing in this permit will be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable federal or state law or regulation. No condition of this permit shall release the permittee from any responsibility or requirements under other environmental statutes or regulations.

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0002 Abrasive Blasting**

Group Members: ARE 0007 ARE 0008 ARE 0009 ARE 0010 ARE 0012

ARE 0007 - All Abrasive Blasting

1 [LAC 33:III.1311.C]

Opacity <= 20 percent; except emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes.

Which Months: All Year Statistical Basis: Six-minute average.

Do not use material derived from hazardous, toxic, medical, and/or municipal waste as abrasive material.

Particulate matter fines < 10 % by weight of the abrasive that would pass through a No. 80 sieve as documented by the supplier. If supplier documentation is not provided for weight percent of fines in abrasive material, take samples according to ASTM standard ASTM D 75-87, reapproved 1992, before initial use.

Which Months: All Year Statistical Basis: None specified

Do not reuse abrasives for abrasive blasting unless they meet the requirements of LAC 33:III.1327.A.2.

Ensure that tarps have overlapping seams to prevent leakage of particulate matter.

Shade factor >= 80 percent. Limit the shade factor of the tarps.

Which Months: All Year Statistical Basis: None specified

Repair tarps prior to use if any single tear greater than 1 foot in length is present or if tears greater than 6 inches in length each are present.

Prevent blasting material or visible floating solids from reaching waters of the state or minimize to the maximum extent possible as specified in the facility and/or activity BMP or in accordance with the LPDES permit program.

Ensure that abrasive blasting activities do not create a nuisance.

Maintain stockpiles of new and/or spent abrasive material in a manner that will minimize fugitive airborne emissions.

Use and diligently maintain all emission control equipment in proper working order according to the manufacturer's specifications whenever any emissions are being generated that can be controlled by the facility, even if the ambient air quality standard in affected areas are not exceeded. Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Maintain the records specified in LAC 33:III.1333.A.1 through A.7 on the facility premises at all times. Present them to an authorized representative of DEQ upon request. Maintain records on a 36 month rolling basis.

ARE 0008 - Abrasive Blasting where object is Fully Enclosed or Surrounded

13 [LAC 33:III.1329.A.1]

Fully enclose the item, or surround the structure, to be blasted.

14 [LAC 33:III.1329.D]

Exhaust the collection system through effective control equipment with a particulate matter outlet grain loading of 0.05 gr/dscf or less, as documented by the control equipment manufacturer or demonstrated by performance testing.

ARE 0009 - Abrasive Blasting Utilizing Best Management Practices

15 [LAC 33:III.1329.A.2]

Prepare and implement a best management practices (BMP) plan as described in LAC 33:III.1331.

Keep a complete copy of the BMP plan at the facility and make available to authorized representatives of DEQ upon request. Submit plans to DEQ if requested by an authorized representative of DEQ.

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities
 Activity Number: PER20090001
 Permit Number: Surface Coating/Fabrication General Master Permit
 Air - Minor Source/Small Source Initial

Group: PCS 0002 Abrasive Blasting**ARE 0009 - Abrasive Blasting Utilizing Best Management Practices**

- 17 [LAC 33:III.1331.C] Designate a person who is accountable for the implementation and effectiveness of the BMP plan.
 Amend the BMP plan if required to by DEQ or whenever physical or operational modification of the facility renders the existing plan inadequate. Implement the amendment prior to or concurrent with the facility modification.
- 18 [LAC 33:III.1331.D] Review the BMP plan every three years to determine if the plan adequately reduces nuisances and adverse off-site impacts. If it is determined that the plan is not adequate, amend the plan within 90 days of the review to include more effective emission prevention and control technology.
- 19 [LAC 33:III.1331.E] Prepare the BMP plan in accordance with sound engineering practices and ensure that it is site-specific. Present the plan information in the sequence specified in LAC 33:III.1331.F.1 through F.10.
- 20 [LAC 33:III.1331.F] Include provisions for personnel training in the BMP plan as specified in LAC 33:III.1331.G.1 through G.4.
- 21 [LAC 33:III.1331.G] Ensure that records of the three year review are signed or initialed by the person conducting the review and an appropriate supervisor or the facility designee. Retain for a minimum of three years.
- 22 [LAC 33:III.1331.H.1] Maintain the following records on the facility premises: Self-inspection reports prepared in accordance with LAC 33:III.1331.F.8, and documentation of employee and contractor training, including dates, subjects, and hours of training and a list of attendees with signatures.
- 23 [LAC 33:III.1331.H.2]

ARE 0010 - Abrasive Blasting Vented Enclosures Subject to NEESHAP XXXXXX

- 24 [40 CFR 63.11516(a)(2)(i)] Operate filtration control device according to manufacturer's instructions. Subpart XXXXXX. [40 CFR 63.11516(a)(2)(i)]
 Capture emissions and vent them to a filtration control device. Subpart XXXXXX. [40 CFR 63.11516(a)(2)(i)]
 Take measures necessary to minimize excess dust in the surrounding area to reduce MFHAP emissions, as practicable. Subpart XXXXXX. [40 CFR 63.11516(a)(2)(ii)(A)]
- 25 [40 CFR 63.11516(a)(2)(ii)(B)] Enclose dusty abrasive material storage areas and holding bins, seal chutes and conveyors that transport abrasive materials. Subpart XXXXXX. [40 CFR 63.11516(a)(2)(ii)(B)]
- 26 [40 CFR 63.11516(a)(2)(ii)(C)] Operate all equipment associated with dry abrasive blasting operations according to manufacturer's instructions. Subpart XXXXXX. [40 CFR 63.11516(a)(2)(ii)(C)]
 Take measures necessary to minimize excess dust in the surrounding area to reduce MFHAP emissions, as practicable. Subpart XXXXXX. [40 CFR 63.11516(a)(3)(i)(A)]
 Enclose abrasive material storage areas and holding bins, seal chutes and conveyors that transport abrasive material. Subpart XXXXXX. [40 CFR 63.11516(a)(3)(i)(B)]
 Operate all equipment associated with dry abrasive blasting operations according to manufacturer's instructions. Subpart XXXXXX. [40 CFR 63.11516(a)(3)(i)(C)]
- 27 [40 CFR 63.11516(a)(2)(ii)(D)] Do not re-use dry abrasive blasting media unless contaminants (i.e., any material other than the base metal, such as paint residue) have been removed by filtration or screening, and the abrasive material conforms to its original size. Subpart XXXXXX. [40 CFR 63.11516(a)(3)(i)(D)]
- 28 [40 CFR 63.11516(a)(2)(ii)(E)] Switch from high particulate matter (PM)-emitting blast media (e.g., sand) to low PM-emitting blast media (e.g., crushed glass, specular hematite, steel shot, aluminum oxide), where PM is a surrogate for MFHAP, whenever practicable. Subpart XXXXXX. [40 CFR 63.11516(a)(3)(i)(E)]
- 29 [40 CFR 63.11516(a)(3)(i)(F)]
- 30 [40 CFR 63.11516(a)(3)(i)(G)]
- 31 [40 CFR 63.11516(a)(3)(i)(H)]
- 32 [40 CFR 63.11516(a)(3)(i)(I)]
- 33 [40 CFR 63.11516(a)(3)(i)(J)]

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0002 Abrasive Blasting****ARE 0010 - Abrasive Blasting Vented Enclosures Subject to NESHAP XXXXX**

- 34 [40 CFR 63.11516(a)(3)(ii)] Visible emissions monitored by 40 CFR 60, Appendix A, Method 22 daily on each day the process is in operation, during the operation of the process. Perform visual determinations at the fenceline or property border nearest to the outdoor dry abrasive blasting operation, for abrasive blasting performed outdoors. Perform visual determinations at the primary vent, stack, exit, or opening from the building containing the abrasive blasting operations, for abrasive blasting performed indoors.

If no visible fugitive emissions are detected in consecutive daily EPA Method 22 tests, performed in accordance with 40 CFR 63.11517(b)(1) for 10 days of work day operation of the process, visible emissions monitored by 40 CFR 60, Appendix A, Method 22 weekly. If visible fugitive emissions are detected during these tests, resume EPA Method 22 testing of that operation once per day during each day that the process is in operation, in accordance with 40 CFR 63.11517(b)(1).

If no visible fugitive emissions are detected in four consecutive weekly EPA Method 22 tests, performed in accordance with 40 CFR 63.11517(b)(2), visible emissions monitored by 40 CFR 60, Appendix A, Method 22 monthly. If visible fugitive emissions are detected during these tests, resume weekly EPA Method 22 tests in accordance with 40 CFR 63.11517(b)(2).

If no visible fugitive emissions are detected in three consecutive monthly EPA Method 22 tests, performed in accordance with 40 CFR 63.11517(b)(3), visible emissions monitored by 40 CFR 60, Appendix A, Method 22 quarterly. If visible fugitive emissions are detected during these tests, resume monthly EPA Method 22 tests in accordance with 40 CFR 63.11517(b)(3). Subpart XXXXXX. [40 CFR 63.11517(b)(1), 40 CFR 63.11516(a)(3)(ii), 40 CFR 63.11517(b)(2), 40 CFR 63.11517(b)(3)]

Which Months: All Year Statistical Basis: None specified

Perform corrective actions until any visible fugitive emissions are eliminated. After visible emissions are eliminated, perform a follow-up inspection for visible fugitive emissions in accordance with 40 CFR 63.11517(a). Subpart XXXXXX. [40 CFR 63.11516(a)(3)(iv)]

Submit Certification and Compliance Report: Due annually, by the 31st of January. Include the information specified in 40 CFR 63.11519(b)(4) through (b)(9), as applicable. Keep the report in a readily-accessible location for inspector review. Submit exceedance report with the certification and compliance report if an exceedance has occurred during the year. Subpart XXXXXX. [40 CFR 63.11519(b)(1)]

Keep records in a form suitable and readily available for expeditious review, according to 40 CFR 63.10(b)(1). Keep each record for 5 years following the date of each occurrence, measurement, corrective action, report, or record. Keep each record on-site for at least 2 years after the date of each occurrence, measurement, corrective action, report, or record according to 40 CFR 63.10(b)(1). The remaining 3 years may be kept off-site. Subpart XXXXXX. [40 CFR 63.11519(c)(15)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]

Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]

All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A as delineated in Table 4 of 40 CFR 63 Subpart XXXXXX.

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0002 Abrasive Blasting****ARE 0012 - Abrasive Blasting Enclosed and Unvented Subject to NESHAP XXXXX**

- 41 [40 CFR 63.11516(a)(1)(i)] Minimize dust generation during emptying of abrasive blasting enclosures. Subpart XXXXXX. [40 CFR 63.11516(a)(1)(i)]
- 42 [40 CFR 63.11516(a)(1)(iii)] Operate all equipment associated with dry abrasive blasting operations according to the manufacturer's instructions. Subpart XXXXXX. [40 CFR 63.11516(a)(1)(iii)]
- 43 [40 CFR 63.11519(b)(1)] Submit Certification and Compliance Report: Due annually, by the 31st of January. Include the information specified in 40 CFR 63.11519(b)(4) through (b)(9), as applicable. Keep the report in a readily-accessible location for inspector review. Submit exceedance report with the certification and compliance report if an exceedance has occurred during the year. Subpart XXXXXX. [40 CFR 63.11519(b)(1)]
- 44 [40 CFR 63.11519(c)(15)] Keep records in a form suitable and readily available for expeditious review, according to 40 CFR 63.10(b)(1). Keep each record for 5 years following the date of each occurrence, measurement, corrective action, report, or record. Keep each record on-site for at least 2 years after the date of each occurrence, measurement, corrective action, report, or record according to 40 CFR 63.10(b)(1). The remaining 3 years may be kept off-site. Subpart XXXXXX. [40 CFR 63.11519(c)(15)]
- 45 [40 CFR 63.11519(c)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]
- 46 [40 CFR 63.11519(c)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]
- 47 [40 CFR 63.] All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A as delineated in Table 4 of 40 CFR 63 Subpart XXXXXX.

Group: PCS 0004 Diesel Internal Combustion Engines

Group Members: EQT 0006EQT 0007EQT 0008

EQT 0005 - All Diesel Engines

- An affected source that is a new or reconstructed stationary source RICE located at an area source must meet the requirements of 40 CFR 63 by meeting the requirements of 40 CFR 60 Subpart III. No further requirements apply for such engines under 40 CFR 63.6590(c). [40 CFR 63.6590(c)]
- Opacity <= 20 percent, except during the cleaning of a fire box or building of a new fire, soot blowing or lancing, charging of an incinerator, equipment changes, ash removal or rapping of precipitators, which may have an opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes (Complies by using sweet natural gas as fuel). Which Months: All Year Statistical Basis: None specified
- Opacity <= 20 percent, except emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes. Which Months: All Year Statistical Basis: Six-minute average

EQT 0006 - Diesel ICEs With Catalytic Controls >= 500 hp & Operating > 720 Hours in Any 6-Month Period and Not Subject to NSPS III

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0004 Diesel Internal Combustion Engines****EQT 0006 - Diesel ICEs With Catalytic Controls >= 500 hp & Operating > 720 Hours in Any 6-Month Period and Not Subject to NSPS III**

- 51 [LAC 33:III.501.C.6] Stack gas concentration: Oxygen monitored by portable analyzer annually (twelve months after the stack test or previous annual test, plus or minus 30 days). Maintain concentrations of O₂ in the same range as during the initial stack test. Calibrate portable analyzers before each test using a known reference gas sample.
- 52 [LAC 33:III.501.C.6] Which Months: All Year Statistical Basis: None specified
Stack gas concentration: Nitrogen oxides monitored by portable analyzer annually (twelve months after the stack test or previous annual test, plus or minus 30 days). Maintain concentrations of NO_x in the same range as during the initial stack test. Calibrate portable analyzers before each test using a known reference gas sample.
- 53 [LAC 33:III.501.C.6] Which Months: All Year Statistical Basis: None specified
Submit report: Due within 60 days after performance/emissions test. Submit emissions test results to the Office of Environmental Assessment. The test results summary shall include any necessary conversion into the units of any applicable Standard. (lbs/MMBtu, gr/dscf, lbs SO₂ / ton 100% H₂SO₄, Etc.) Plant and in house laboratory data to support production values shall be included. (Example: how many tons of 100% equivalent H₂SO₄ was being produced) Units tested at less than 95% of permitted maximum capacity shall provide documentation to support compliance at 100% of the permitted maximum capacity.
- 54 [LAC 33:III.501.C.6] Stack gas concentration: Carbon monoxide monitored by portable analyzer annually (twelve months after the stack test or previous annual test, plus or minus 30 days). Maintain concentrations of CO in the same range as during the initial stack test. Calibrate portable analyzers before each test using a known reference gas sample.
- 55 [LAC 33:III.501.C.6] Which Months: All Year Statistical Basis: None specified
Equipment/operational data recordkeeping by electronic or hard copy annually. Recorded parameters are NO_x, CO, and O₂ concentrations in the stack gas obtained during annual testing.
- 56 [LAC 33:III.501.C.6] Conduct a performance/emissions test: Due within 180 days after initial startup (or restart-up after modification), or within 60 days after achieving normal production rate or end of the shutdown period, whichever is earliest. The stack test's purpose is to demonstrate compliance with the emission limits of this permit and therefore must be conducted at greater than 80% of maximum permitted capacity. Repeat the test after each major engine overhaul. Test methods and procedures shall be in accordance with New Source Performance Standards, 40 CFR 60, Appendix A, Method 7E - Determination of Nitrogen Oxides Emissions from Stationary Sources and Method 10 - Determination of Carbon Monoxide Emissions from Stationary Sources. Use alternate stack test methods only with the prior approval of the Office of Environmental Assessment, Environmental Technology Division, Engineering Services. As required by LAC 33:III.913, provide necessary sampling ports in stacks or ducts and such other safe and proper sampling and testing facilities for proper determination of the emission limits.
- 57 [LAC 33:III.501.C.6] Submit notification: Due at least 30 days prior to any LDEQ required performance/emissions test to the Office of Environmental Assessment, to provide the opportunity to conduct a pretest meeting and observe the emission testing.

EQT 0007 - Diesel ICEs Without Catalytic Controls >= 500 hp & Operating > 720 Hours in Any 6-Month Period and Not Subject to NSPS III

- 58 [LAC 33:III.501.C.6] Option 1: Stack gas concentration: Oxygen monitored by portable analyzer semiannually (six months after the stack test or previous semiannual test, plus or minus 30 days). Maintain concentrations of O₂ in the same range as during the initial stack test. Calibrate portable analyzers before each test using a known reference gas sample.
- Which Months: All Year Statistical Basis: None specified

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0004 Diesel Internal Combustion Engines****EQT 0007 - Diesel ICEs Without Catalytic Controls >= 500 hp & Operating > 720 Hours in Any 6-Month Period and Not Subject to NSPS III**

59 [LAC 33:III.501.C.6]

Option 1: Stack gas concentration: Carbon monoxide monitored by portable analyzer semiannually (six months after the stack test or previous semiannual test, plus or minus 30 days). Maintain concentrations of CO in the same range as during the initial stack test. Calibrate portable analyzers before each test using a known reference gas sample.

60 [LAC 33:III.501.C.6]

Which Months: All Year Statistical Basis: None specified
Option 2: Equipment/operational data monitored by portable analyzer daily at manned stations, otherwise weekly. Maintain monitored parameters (intake manifold temperature and pressure, fuel header pressure, fuel rack position (fuel flow), and injector timing) in the same range as during the initial stack test.

61 [LAC 33:III.501.C.6]

Which Months: All Year Statistical Basis: None specified

Submit notification: Due at least 30 days prior to any LDEQ required performance/emissions test to the Office of Environmental Assessment, to provide the opportunity to conduct a pretest meeting and observe the emission testing.

62 [LAC 33:III.501.C.6]

Option 2: Equipment/operational data recordkeeping by electronic or hard copy daily at manned stations, otherwise weekly. Recorded parameters are intake manifold temperature and pressure, fuel header pressure, diesel rack position (fuel flow), and injector timing.

63 [LAC 33:III.501.C.6]

Option 1: Equipment/operational data recordkeeping by electronic or hard copy semiannually. Recorded parameters are NOx, CO, O2, SO2 and VOC concentrations in the stack gas obtained during semiannual testing.

64 [LAC 33:III.501.C.6]

Option 1: Stack gas concentration: Nitrogen oxides monitored by portable analyzer semiannually (six months after the stack test or previous semiannual test, plus or minus 30 days). Maintain concentrations of NOx in the same range as during the initial stack test. Calibrate portable analyzers before each test using a known reference gas sample.

65 [LAC 33:III.501.C.6]

Which Months: All Year Statistical Basis: None specified
Submit report: Due within 60 days after performance/emissions test. Submit emissions test results to the Office of Environmental Assessment. The test results summary shall include any necessary conversion into the units of any applicable Standard. (lbs/MMBtu, gr/dscf, lbs SO2 / ton H2SO4, Etc.) Plant and in house laboratory data to support production values shall be included. (Example: how many tons of 100% equivalent H2SO4 was being produced) Units tested at less than 95% of permitted maximum capacity shall provide documentation to support compliance at 100% of the permitted maximum capacity.

66 [LAC 33:III.501.C.6]

Conduct a performance/emissions test: Due within 180 days after initial startup (or restart-up after modification), or within 60 days after achieving normal production rate or end of the shutdown period, whichever is earliest. The stack test's purpose is to demonstrate compliance with the emission limits of this permit and therefore must be conducted at greater than 80% of maximum permitted capacity. Repeat the test after each major engine overhaul. Test methods and procedures shall be in accordance with New Source Performance Standards, 40 CFR 60, Appendix A, Method 7E - Determination of Nitrogen Oxides Emissions from Stationary Sources and Method 10 - Determination of Carbon Monoxide Emissions from Stationary Sources. Use alternate stack test methods only with the prior approval of the Office of Environmental Assessment, Environmental Technology Division, Engineering Services. As required by LAC 33:III.9i3, provide necessary sampling ports in stacks or ducts and such other safe and proper sampling and testing facilities for proper determination of the emission limits.

EQT 0008 - Diesel ICEs - Engines Subject to NSPS III

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0004 Diesel Internal Combustion Engines**EQT 0008 - Diesel ICEs - Engines Subject to NSPS III**

- 67 [40 CFR 60.4204(a)] Pre-2007 year Models, Non-Emergency Use, ≥ 10 L/cylinder < 30 L/cylinder, and Max Test Speed ≥ 2000 RPM: Nitrogen oxides ≤ 7.3 g/BHP-hr (9.8 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and < 11 HP: Non-methane hydrocarbons plus Nitrogen oxides ≤ 7.8 g/BHP-hr (10.5 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and ≥ 175 HP: Total hydrocarbon ≤ 1.0 g/BHP-hr (1.3 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and ≥ 11 HP < 50 HP: Particulate matter (10 microns or less) ≤ 0.60 g/BHP-hr (0.80 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and ≥ 25 HP < 50 HP: Carbon monoxide ≤ 4.1 g/BHP-hr (5.5 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and ≥ 11 HP < 50 HP: Non-methane hydrocarbons plus Nitrogen oxides ≤ 7.1 g/BHP-hr (9.5 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and ≥ 11 HP: Carbon monoxide ≤ 6.0 g/BHP-hr (8.0 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and ≥ 11 HP < 25 HP: Carbon monoxide ≤ 4.9 g/BHP-hr (6.6 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and ≥ 11 HP < 50 HP: Nitrogen oxides ≤ 6.9 g/BHP-hr (9.2 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, > 10 L/cylinder < 30 L/cylinder, and Max Test Speed < 130 RPM: Nitrogen oxides ≤ 12.7 g/BHP-hr (17.0 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and ≥ 11 HP: Particulate matter (10 microns or less) ≤ 0.75 g/BHP-hr (1.0 g/KW-hr). Subpart III. [40 CFR 60.4204(a)]
Which Months: All Year Statistical Basis: None specified
Pre-2007 year Models, Non-Emergency Use, > 10 L/cylinder < 30 L/cylinder, and Max Test Speed ≥ 130 RPM: Nitrogen oxides $\leq 33.6 \times N^{<20}$ g/BHP-hr (45.0 $\times N^{<20}$ g/KW-hr), where N is the appropriate maximum test speed in RPM. Note: Round speed-dependent standards to the nearest 0.1 g/BHP-hr.) Subpart III. [40 CFR 60.4204(a)]

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0004 Diesel Internal Combustion Engines**EQT 0008 - Diesel ICEs - Engines Subject to NSPS III**

- 79 [40 CFR 60.4204(a)] Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and >= 175 HP: Particulate matter (10 microns or less) <= 0.40 g/BHP-hr (0.54 g/KW-hr). Subpart III. [40 CFR 60.4204(a)] Which Months: All Year Statistical Basis: None specified
- 80 [40 CFR 60.4204(a)] Pre-2007 year Models, Non-Emergency Use, < 10 L/cylinder, and >= 175 HP: Carbon monoxide <= 8.5 g/BHP-hr (11.4 g/KW-hr). Subpart III. [40 CFR 60.4204(a)] Which Months: All Year Statistical Basis: None specified
- 81 [40 CFR 60.4204(b)] >= 2007 year Models, Non-Emergency Use, and < 30 L/cylinder: Comply with the emission standards for new CI engines in 40 CFR 60.4201, as applicable. Subpart III. [40 CFR 60.4204(b)] All Models, Non-Emergency Use, and >= 30 L/cylinder (Option 2): Nitrogen oxides <= 1.2 g/BHP-hr (1.6 g/KW-hr). Subpart III. [40 CFR 60.4204(c)(1)] Which Months: All Year Statistical Basis: None specified
- 82 [40 CFR 60.4204(c)(1)] All Models, Non-Emergency Use, and >= 30 L/cylinder (Option 2): Nitrogen oxides <= 0.11 g/BHP-hr (0.15 g/KW-hr). Subpart III. [40 CFR 60.4204(c)(1)] Which Months: All Year Statistical Basis: None specified
- 83 [40 CFR 60.4204(c)(1)] All Models, Non-Emergency Use, and >= 30 L/cylinder (Option 1): Nitrogen oxides >= 90 % reduction. Subpart III. [40 CFR 60.4204(c)(1)] Which Months: All Year Statistical Basis: None specified
- 84 [40 CFR 60.4204(c)(2)] All Models, Non-Emergency Use, and >= 30 L/cylinder (Option 2): Particulate matter (10 microns or less) <= 0.11 g/BHP-hr (0.15 g/KW-hr). Subpart III. [40 CFR 60.4204(c)(2)] Which Months: All Year Statistical Basis: None specified
- 85 [40 CFR 60.4204(c)(2)] All Models, Non-Emergency Use, and >= 30 L/cylinder (Option 1): Particulate matter (10 microns or less) >= 60 % reduction. Subpart III. [40 CFR 60.4204(c)(2)] Which Months: All Year Statistical Basis: None specified
- 86 [40 CFR 60.4205(a)] Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and >= 25 HP < 50 HP: Carbon monoxide <= 4.1 g/BHP-hr (5.5 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
- 87 [40 CFR 60.4205(a)] Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and < 11 HP: Particulate matter (10 microns or less) <= 0.75 g/BHP-hr (1.0 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
- 88 [40 CFR 60.4205(a)] Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and < 11 HP: Non-methane hydrocarbons plus Nitrogen oxides <= 7.8 g/BHP-hr (10.5 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
- 89 [40 CFR 60.4205(a)] Pre-2000 RPM, Emergency Use excluding Fire Pump Engines, >= 10 L/cylinder < 30 L/cylinder, and Max Test Speed >= 130 RPM < 2000 RPM: Nitrogen oxides <= $33.6 \times N^2 \times 20 \text{ g/BHP-hr}$ ($45.0 \times N^2 \times 20 \text{ g/KW-hr}$), where N is the appropriate maximum test speed in RPM.
- Note: Round speed-dependent standards to the nearest 0.1 g/BHP-hr. Subpart III. [40 CFR 60.4205(a)]
- 90 [40 CFR 60.4205(a)] Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, >= 10 L/cylinder < 30 L/cylinder, and Max Test Speed >= 2000 RPM: Nitrogen oxides <= 7.3 g/BHP-hr (9.8 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities
 Activity Number: PER20090001
 Permit Number: Surface Coating/Fabrication General Master Permit
 Air - Minor Source/Small Source Initial

Group: PCS 0004 Diesel Internal Combustion Engines**EQT 0008 - Diesel ICEs - Engines Subject to NSPS III**

91	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and >= 11 HP < 25 HP: Carbon monoxide <= 4.9 g/BHP-hr (6.6 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
92	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and >= 175 HP: Carbon monoxide <= 8.5 g/BHP-hr (11.4 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
93	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and >= 11 HP < 50 HP: Particulate matter (10 microns or less) <= 0.60 g/BHP-hr (0.80 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
94	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, >= 10 L/cylinder < 30 L/cylinder, and Max Test Speed < 130 RPM: Nitrogen oxides <= 12.7 g/BHP-hr (17.0 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
95	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and >= 11 HP < 50 HP: Non-methane hydrocarbons plus Nitrogen oxides <= 7.1 g/BHP-hr (9.5 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
96	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and >= 175 HP: Total hydrocarbon <= 1.0 g/BHP-hr (1.3 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
97	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and >= 175 HP: Particulate matter (10 microns or less) <= 0.40 g/BHP-hr (0.54 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
98	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and >= 11 HP < 50 HP: Nitrogen oxides <= 6.9 g/BHP-hr (9.2 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
99	[40 CFR 60.4205(a)]	Pre-2007 year Models, Emergency Use excluding Fire Pump Engines, < 10 L/cylinder, and < 11 HP: Carbon monoxide <= 6.0 g/BHP-hr (8.0 g/KW-hr). Subpart III. [40 CFR 60.4205(a)] Which Months: All Year Statistical Basis: None specified
100	[40 CFR 60.4205(b)]	>= 2007 year Models, Emergency Use excluding Fire Pump Engines, and < 30 L/cylinder: Comply with the emission standards for new nonroad CI engines in 40 CFR 60.4202, for all pollutants, for the same model year and maximum engine power. Subpart III. [40 CFR 60.4205(b)] Fire Pump Engines, < 30 L/cylinder, <= 11 HP < 50 HP: Non-methane hydrocarbons plus Nitrogen oxides <= 7.1 g/BHP-hr (9.5 g/KW-hr). Subpart III. [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
101	[40 CFR 60.4205(c)]	Fire Pump Engines, < 30 L/cylinder, <= 2010 year Models, and >= 2010 year Models, < 30 L/cylinder, <= 2010 year Models, and >= 25 HP < 50 HP: Carbon monoxide <= 4.1 g/BHP-hr (5.5 g/KW-hr). Subpart III. [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0004 Diesel Internal Combustion Engines**EQT 0008 - Diesel ICEs - Engines Subject to NSPS III**

- 103 [40 CFR 60.4205(c)] Fire Pump Engines; < 30 L/cylinder; and >= 2010 year Models and >= 100 HP < 175 HP, or >= 2009 year Models and >= 175 HP < 750 HP; Non-methane hydrocarbons plus Nitrogen oxides <= 3.0 g/BHP-hr (4.0 g/KW-hr). Note: 2009-2012 year models that are >= 100 HP < 600 HP with rated speed of > 2,650 rpm may comply with the emission limitations for 2008 - 2009 year models of the same capacity. Subpart III. [40 CFR 60.4205(c)]
- 104 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines, < 30 L/cylinder; <= 2010 year Models, and >= 11 HP < 25 HP: Carbon monoxide <= 4.9 g/BHP-hr (6.6 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
- 105 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines, < 30 L/cylinder; <= 2010 year Models, and < 11 HP: Carbon monoxide <= 6.0 g/BHP-hr (8.0 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
- 106 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines, < 30 L/cylinder; <= 2010 year Models, and < 11 HP: Particulate matter (10 microns or less) <= 0.75 g/BHP-hr (1.0 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
- 107 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines; < 30 L/cylinder; <= 2010 year Models and >= 50 HP < 100 HP, or <= 2009 year Models and >= 100 HP < 175 HP; Carbon monoxide <= 3.7 g/BHP-hr (5.0 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
- 108 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines, < 30 L/cylinder; >= 2008 year Models, and >= 750 HP: Non-methane hydrocarbons plus Nitrogen oxides <= 4.8 g/BHP-hr (6.4 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
- 109 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines, < 30 L/cylinder; >= 2011 year Models, and < 25 HP or >= 50 HP < 100 HP: Particulate matter (10 microns or less) <= 0.30 g/BHP-hr (0.40 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
- 110 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines; < 30 L/cylinder; and >= 25 HP < 50 HP, or >= 2010 year Models and >= 100 HP < 175 HP; Particulate matter (10 microns or less) <= 0.22 g/BHP-hr (0.30 g/KW-hr). Note: 2010-2012 year models that are >= 100 HP < 175 HP with rated speed of > 2,650 rpm may comply with the emission limitations for 2009 year models of the same capacity. Subpart III. [40 CFR 60.4205(c)]
- 111 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines; < 30 L/cylinder; and <= 2010 year Models and < 11 HP or >= 50 HP < 100 HP, or <= 2009 year Models and >= 100 HP < 175 HP, or <= 2008 year Models and >= 175 HP <= 750 HP, or <= 2007 year Models and > 750 HP: Non-methane hydrocarbons plus Nitrogen oxides <= 7.8 g/BHP-hr (10.5 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
- 112 [40 CFR 60.4205(c)] Which Months: All Year Statistical Basis: None specified
Fire Pump Engines, < 30 L/cylinder; >= 2011 year Models, and < 50 HP: Non-methane hydrocarbons plus Nitrogen oxides <= 5.6 g/BHP-hr (7.5 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
- Which Months: All Year Statistical Basis: None specified

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0004 Diesel Internal Combustion Engines****EQT 0008 - Diesel ICEs - Engines Subject to NSPS III**

- 113 [40 CFR 60.4205(c)] Fire Pump Engines; < 30 L/cylinder, and <= 2008 year Models and >= 175 HP < 750 HP, or <= 2007 year Models and > 750 HP: Carbon monoxide <= 2.6 g/BHP-hr (3.5 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
Which Months: All Year Statistical Basis: None specified
- 114 [40 CFR 60.4205(c)] Fire Pump Engines, < 30 L/cylinder, and <= 2010 year Models and >= 11 HP < 175 HP or <= 2009 year Models >= 100 HP < 175 HP:
Particulate matter (10 microns or less) <= 0.60 g/BHP-hr (0.80 g/KW-hr). Subpart III. [40 CFR 60.4205(c)]
Which Months: All Year Statistical Basis: None specified
- 115 [40 CFR 60.4205(c)] Fire Pump Engines, < 30 L/cylinder, >= 2011 year Models, and >= 50 HP < 100 HP: Non-methane hydrocarbons plus Nitrogen oxides <= 3.5 g/BHP-hr (4.7 g/KW-hr). Note: 2011-2013 year models that are >= 50 HP < 100 HP with rated speed of > 2,650 rpm may comply with the emission limitations for 2010 year models of the same capacity. Subpart III. [40 CFR 60.4205(c)]
Which Months: All Year Statistical Basis: None specified
- 116 [40 CFR 60.4205(c)] Fire Pump Engines; < 30 L/cylinder, and >= 2009 year Models and >= 175 HP < 750 HP, or >= 2008 year Models and > 750 HP: Particulate matter (10 microns or less) <= 0.15 g/BHP-hr (0.20 g/KW-hr). Note: 2009-2011 year models that are >= 175 HP < 600 HP with rated speed of > 2,650 rpm may comply with the emission limitations for 2008 year models of the same capacity. Subpart III. [40 CFR 60.4205(c)]
Which Months: All Year Statistical Basis: None specified
- 117 [40 CFR 60.4205(c)] Fire Pump Engines; < 30 L/cylinder, and <= 2008 year Models and >= 175 HP < 750 HP, or <= 2007 year Models and > 750 HP: Particulate matter (10 microns or less) <= 0.40 g/BHP-hr (0.54 g/KW-hr). Note: 2011-2013 year models that are >= 50 HP < 100 HP with rated speed of > 2,650 rpm may comply with the emission limitations for 2010 year models of the same capacity. [40 CFR 60.4205(c)]
Which Months: All Year Statistical Basis: None specified
- 118 [40 CFR 60.4205(d)(1)] All Models, All Emergency Use, and >= 30 L/cylinder (Option 1): Nitrogen oxides >= 90 % reduction. Subpart III. [40 CFR 60.4205(d)(1)]
Which Months: All Year Statistical Basis: None specified
- 119 [40 CFR 60.4205(d)(1)] All Models, All Emergency Use, and >= 30 L/cylinder (Option 2): Nitrogen oxides <= 1.2 g/BHP-hr (1.6 g/KW-hr). Subpart III. [40 CFR 60.4205(d)(1)]
Which Months: All Year Statistical Basis: None specified
- 120 [40 CFR 60.4205(d)(2)] All Models, All Emergency Use, and >= 30 L/cylinder (Option 1): Particulate matter (10 microns or less) >= 60 % reduction. Subpart III. [40 CFR 60.4205(d)(2)]
Which Months: All Year Statistical Basis: None specified
- 121 [40 CFR 60.4205(d)(2)] All Models, All Emergency Use, and >= 30 L/cylinder (Option 2): Particulate matter (10 microns or less) <= 0.11 g/BHP-hr (0.15 g/KW-hr). Subpart III. [40 CFR 60.4205(d)(2)]
Which Months: All Year Statistical Basis: None specified
- 122 [40 CFR 60.4206] Operate and maintain stationary CIICE according to the manufacturer's written instructions or procedures developed by the owner or operator that are approved by the engine manufacturer, over the entire life of the engine. Subpart III.
Beginning October 1, 2007, use diesel fuel that meets the requirements of 40 CFR 80.510(a). Subpart III. [40 CFR 60.4207(a)]
Beginning October 1, 2010, use diesel fuel that meets the requirements of 40 CFR 80.510(b) for nonroad diesel fuel. Subpart III. [40 CFR 60.4207(b)]
Comply with all applicable deadlines specified in 40 CFR 60.4208(a) through (h). Subpart III.

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0004 Diesel Internal Combustion Engines****EQT 0008 - Diesel ICEs - Engines Subject to NSPS III**

- 126 [40 CFR 60.4209(a)] All Models, All Emergency Use, All Displacements: Operating time monitored by hour/time monitor continuously during operation. Install a non-resettable hour meter prior to startup of the engine. Subpart III. [40 CFR 60.4209(a)]
- Which Months: All Year Statistical Basis: None specified
- Engines Equipped w/ Diesel Particulate Filter: Pressure monitored by pressure instrument continuously during operation. Install a backpressure monitor on the diesel particulate filter that notifies the owner or operator when the high backpressure limit of the engine is approached. Subpart III. [40 CFR 60.4209(b)]
- Which Months: All Year Statistical Basis: None specified
- Operate and maintain the stationary CI internal combustion engine and control device according to the manufacturer's written instructions or procedures developed by the owner or operator that are approved by the engine manufacturer. In addition, only change those settings that are permitted by the manufacturer. Also meet the requirements of 40 CFR 89, 94 and/or 1068, as applicable. Subpart III. [40 CFR 60.4211(a)] < 30 L/cylinder, All Uses, and Pre-2007 year Models, as well as Fire Pump Engines < 100 HP built before 2011 or >= 100 HP < 175 HP built before 2010 or >= 175 HP < 750 built before 2009 or > 750 HP built before 2008: Demonstrate compliance according to one of the methods specified in 40 CFR 60.4211(b)(1) through (b)(5). Subpart III. [40 CFR 60.4211(b)]
- < 30 L/cylinder, All Uses, and >= 2007 year Models except for Fire Pump Engines < 100 HP built before 2011 or >= 100 HP < 175 HP built before 2010 or >= 175 HP < 750 built before 2008: Ensure engine is certified to the emission standards in 40 CFR 60.4204(b), or 40 CFR 60.4025(b) or (c), as applicable, for the same model year and maximum (or in the case of fire pumps, NFPA nameplate) engine power. Install and configure according to the manufacturer's specifications. Subpart III. [40 CFR 60.4211(c)]
- All Models, All Uses, and >= 30 L/cylinder: Conduct an initial performance test to demonstrate initial compliance with the emission standards as specified in 40 CFR 60.4213. Subpart III. [40 CFR 60.4211(d)(1)]
- All Models, All Uses, and >= 30 L/cylinder: Submit petition to LDEQ for approval of operating parameters to be monitored continuously. Include the information described in 40 CFR 60.4211(d)(2)(i) through (d)(2)(v). Subpart III. [40 CFR 60.4211(d)(2)]
- All Models, All Uses, and >= 30 L/cylinder: Equipment/operational data monitored by technically sound method continuously. Subpart III. [40 CFR 60.4211(d)(2)]
- Which Months: All Year Statistical Basis: None specified
- All Models, Non-Emergency Use, and >= 30 L/cylinder: Conduct annual performance tests to demonstrate continuous compliance with the emission standards as specified in 40 CFR 60.4213. Subpart III. [40 CFR 60.4211(d)(3)]
- All Emergency Use and All Displacements: Operate for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by Federal, State or local government, the manufacturer, the vendor, or the insurance company associated with the engine. Limit maintenance checks and readiness testing to 100 hours per year. There is no time limit during use in emergency situations. A petition for approval of additional hours to be used for maintenance checks and readiness testing may be submitted to LDEQ, but a petition is not required if records are maintained indicating that Federal, State, or local standards require maintenance and testing of emergency engines beyond 100 hours per year. Any operation other than emergency operations, and maintenance and testing as allowed per 40 CFR 60.4211(e) for emergency engines subject to standards under 40 CFR 60.4205, is prohibited. Subpart III. [40 CFR 60.4211(e)]
- Engines subject to 40 CFR 62.4211(b): Conduct performance tests according to 40 CFR 60.4212(a) through (d). Subpart III.

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0004 Diesel Internal Combustion Engines****EQT 0008 - Diesel ICEs - Engines Subject to NSPS III**

- 137 [40 CFR 60.4213(d)] Engines subject to 40 CFR 62.4211(d) complying with percent reductions per 40 CFR 60.4204(c) or 4205(d); Determine compliance with the percent reduction requirement using the methods and procedures specified in 40 CFR 60.4213(g)(1) through (d)(3). Subpart III. [40 CFR 60.4213(d)]
- 138 [40 CFR 60.4213(e)] Engines subject to 40 CFR 62.4211(d) complying with NOx mass/unit output limit per 40 CFR 60.4204(c) or 4205(d); Determine compliance with the NOx mass per unit output emission limitation by converting the concentration of NOx in engine exhaust using 40 CFR 60.4213(e), Equation 7. Subpart III. [40 CFR 60.4213(e)]
- 139 [40 CFR 60.4213(f)] Engines subject to 40 CFR 62.4211(d) complying with PM mass/unit output limit per 40 CFR 60.4204(c) or 4205(d); Determine compliance with the PM mass per unit output emission limitation by converting the concentration of PM in the engine exhaust using 40 CFR 60.4213(f), Equation 8. Subpart III. [40 CFR 60.4213(f)]
- 140 [40 CFR 60.4213] Engines subject to 40 CFR 62.4211(d); Conduct performance tests according to 40 CFR 60.4213(a) through (c). Subpart III.
- 141 [40 CFR 60.4214(a)(1)] Non-Emergency Use, and > 3,000 HP or $\geq 10 \text{ L/cylinder}$ or Non-Certified Pre-2007 year Models > 175 HP: Submit an initial notification as required in 40 CFR 60.7(a)(1). Include the information in 40 CFR 60.4214(a)(1)(iv). Subpart III. [40 CFR 60.4214(a)(1)]
- 142 [40 CFR 60.4214(a)(2)] Non-Emergency Use, and > 3,000 HP or $\geq 10 \text{ L/cylinder}$ or Non-Certified Pre-2007 year Models > 175 HP: Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information in 40 CFR 60.4214(a)(2)(i) through (a)(2)(iv). Subpart III. [40 CFR 60.4214(a)(2)]
- 143 [40 CFR 60.4214(b)] Emergency Use and ≥ 2011 year Model: Operating time recordkeeping by electronic or hard copy upon occurrence of event. If the emergency engine does not meet the standards applicable to non-emergency engines in the applicable model year, keep records of the operation of the engine in emergency and non-emergency service that are recorded through the non-resettable hour meter. Record the time of operation of the engine and the reason the engine was in operation during that time. Subpart III. [40 CFR 60.4214(b)]
- 144 [40 CFR 60.4214(c)] Engines Equipped with Diesel Particulate Filter: Equipment/operational data recordkeeping by electronic or hard copy upon occurrence of event. Keep records of any corrective action taken after the backpressure monitor has notified the owner or operator that the high backpressure limit of the engine is approached. Subpart III. [40 CFR 60.4214(c)]

Group: PCS 0001 Surface Coating

Group Members: ARE 0001 ARE 0002 ARE 0003 ARE 0004 ARE 0005 ARE 0006

ARE 0001 - All Surface Coating

- 145 [LAC 33.III.1305] Prevent particulate matter from becoming airborne by taking all reasonable precautions. These precautions shall include, but not be limited to, those specified in LAC 33.III.1305.A.1-7.
- 146 [LAC 33.III.1311.C] Opacity ≤ 20 percent; except emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes.
- Which Months: All Year Statistical Basis: Six-minute average

ARE 0002 - Surface Coating Subject to LAC 33.III.2123

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0001 Surface Coating**ARE 0002 - Surface Coating Subject to LAC 33:III.2123**

- 147 [LAC 33:III.2123.A] Reduce emissions, where feasible, by incineration, provided 90 percent of the carbon in the organic compounds being incinerated is oxidized to carbon dioxide (except as provided in LAC 33:III.2123.D); carbon adsorption of the organic compounds; or any other equivalent means as may be approved by DEQ.
- 148 [LAC 33:III.2123.C.10] Factory surface coating of flat wood paneling. Natural finish hardwood plywood panels: VOC, Total: <= 12.0 lbs/1000 ft² (5.8 Kgs/100 m²) of coated surface.
- 149 [LAC 33:III.2123.C.10] Factory surface coating of flat wood paneling. Printed interior wall panels made of hardwood plywood and thin particleboard: VOC, Total: <= 6.0 lbs/1000 ft² (2.9 Kgs/100 m²) of coated surface.
- 150 [LAC 33:III.2123.C.10] Factory surface coating of flat wood paneling. Class II finishes for hardboard paneling: VOC, Total: <= 6.0 lbs/1000 ft² (2.9 Kgs/100 m²) of coated surface.
- 151 [LAC 33:III.2123.C.11.a] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Two component coatings: VOC, Total <= 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 152 [LAC 33:III.2123.C.11.a] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Baked Coatings: VOC, Total <= 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 153 [LAC 33:III.2123.C.11.a] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Air-dried single-component alkyd or vinyl flat or semi-gloss finish coatings: VOC, Total <= 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 154 [LAC 33:III.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Preconstruction and Interior Primer Coating: VOC, Total <= 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 155 [LAC 33:III.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment in the following parishes: Ascension, Calcasieu, East Baton Rouge, Iberville, Livingston, Pointe Coupee, and West Baton Rouge: VOC, Total <= 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 156 [LAC 33:III.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Special Marking Coating: VOC, Total <= 4.08 lb/gal (0.49 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 157 [LAC 33:III.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Flight Deck Markings (DOD-C-24667) Coating: VOC, Total <= 4.2 lb/gal (0.504 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 158 [LAC 33:III.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Metallic Heat Resistant Coating: VOC, Total <= 4.42 lb/gal (0.53 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0001 Surface Coating**ARE 0002 - Surface Coating Subject to LAC 33:II.2123**

- 159 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Sealant for Wire-Sprayed Aluminum Coating: VOC, Total $\leq 5.4 \text{ lb/gal}$ (0.648 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 160 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Low Activation Interior Coating: VOC, Total $\leq 4.08 \text{ lb/gal}$ (0.49 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 161 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Antenna Coating: VOC, Total $\leq 4.42 \text{ lb/gal}$ (0.53 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 162 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Heat Resistant Coating: VOC, Total $\leq 3.5 \text{ lb/gal}$ (0.42 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 163 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Dull Black Finish Coating (DOD-P-15146): VOC, Total $\leq 3.7 \text{ lb/gal}$ (0.444 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 164 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Repair and Maintenance Thermoplastic Coating: VOC, Total $\leq 5.41 \text{ lb/gal}$ (0.65 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 165 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Solvent-Based Inorganic Zinc Primer Coating: VOC, Total $\leq 5.41 \text{ lb/gal}$ (0.65 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 166 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Antifoulant Applied to Aluminum Hulls Coating: VOC, Total $\leq 4.5 \text{ lb/gal}$ (0.55 kg/L) of coating as applied (minus water and exempt solvent), in accordance with B.(1) of the Louisiana Shipbuilding & Ship Repair Facilities and Outdoor Surface Coating of Large Structures MACT Determination (November 23, 1995). Include organic compounds contained in the paint or thinner which have negligible photochemical reactivity but are listed in LAC 33:III.Table 51.1. Which Months: All Year Statistical Basis: Daily average
- 167 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Navigational Aids Coating: VOC, Total $\leq 3.5 \text{ lb/gal}$ (0.42 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 168 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Potable Water Tank Coating (DOD-P-23236): VOC, Total $\leq 3.7 \text{ lb/gal}$ (0.444 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 169 [LAC 33:II.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Antifoulant Coating: VOC, Total $\leq 3.66 \text{ lb/gal}$ (0.44 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0001 Surface Coating****ARE 0002 - Surface Coating Subject to LAC 33:III.2123**

170 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Vinyl Acrylic Top Coats Coating: VOC, Total \leq 5.4 lb/gal (0.648 kg/L) of coating as applied (minus water and exempt solvent), in accordance with B.(1) of the Louisiana Shipbuilding & Ship Repair Facilities and Outdoor Surface Coating of Large Structures MACT Determination (November 23, 1995). Include organic compounds contained in the paint or thinner which have negligible photochemical reactivity but are listed in LAC 33:III.Table 51.1.

171 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. High Gloss Alkyd Coating: VOC, Total \leq 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

172 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. High Temperature (Fed. Spec. TT-P-28) Coating: VOC, Total \leq 5.41 lb/gal (0.65 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

173 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Underwater Weapon Coating: VOC, Total \leq 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

174 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Tank Coating (DOD-P-23236): VOC, Total \leq 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

175 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Tack Coat (Epoxies) Coating: VOC, Total \leq 5.08 lb/gal (0.61 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

176 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Elastomeric Adhesives with 15% weight Natural or Synthetic Rubber Coating: VOC, Total \leq 6.08 lb/gal (0.73 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

177 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Exterior Epoxy Primer Coating: VOC, Total \leq 3.5 lb/gal (0.42 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

178 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Wood Spar Varnish (Fed. Spec. TT-V-119) Coating: VOC, Total \leq 4.1 lb/gal (0.492 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

179 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Extreme High Gloss Coating: VOC, Total \leq 4.08 lb/gal (0.49 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

180 [LAC 33:III.2123.C.11.b]

Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Anchor Chain Asphalt Varnish (Fed. Spec. TT-V-51) Coating: VOC, Total \leq 5.2 lb/gal (0.62 kg/L) of coating as applied (minus water and exempt solvent).

Which Months: All Year Statistical Basis: Daily average

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0001 Surface Coating**ARE 0002 - Surface Coating Subject to LAC 33:III.2123**

- 181 [LAC 33:III.2123.C.11.b] Surface coating for marine vessels and oilfield tubulars and ancillary oilfield equipment. Pretreatment Wash Primer Coating: VOC, Total <= 6.5 lb/gal (0.78 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Large appliance coating. Applies to prime, single, topcoat application area, flashoff area, and oven: VOC, Total <= 2.8 lb/gal (0.34 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of cans. End sealing compound: VOC, Total <= 3.7 lb/gal (0.44 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of cans. Two and three-piece can interior body spray, two-piece can exterior end (spray or roll coat): VOC, Total <= 4.2 lb/gal (0.51 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of cans. Three-piece can side seam spray: VOC, Total <= 5.5 lb/gal (0.66 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of cans. Sheet basecoat (exterior and interior) and over-varnish: Two-piece can exterior (basecoat and over-varnish): VOC, Total <= 2.8 lb/gal (0.34 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of Coils. Prime and topcoat or single coat operations: VOC, Total <= 2.6 lb/gal (0.31 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of paper. Coating line: VOC, Total <= 2.9 lb/gal (0.35 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of fabrics. Vinyl coating line (except Plasticol coating): VOC, Total <= 3.8 lb/gal (0.45 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of fabrics. Coating line: VOC, Total <= 2.9 lb/gal (0.35 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of assembly line automobiles and light duty trucks. Prime application, flashoff area and oven (determined on a monthly basis): VOC, Total <= 1.2 lb/gal (0.14 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of assembly line automobiles and light duty trucks. Final repair application, flashoff area and oven: VOC, Total <= 4.8 lb/gal (0.58 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average Surface coating of assembly line automobiles and light duty trucks. Topcoat application, flashoff area and oven: VOC, Total <= 2.8 lb/gal (0.34 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0001 Surface Coating****ARE 0002 - Surface Coating Subject to LAC 33:III.2123**

- 194 [LAC 33:III.2.123.C.6] Surface coating of assembly line automobiles and light duty trucks. Primer surface application flashoff area and oven: VOC, Total $\leq 2.8 \text{ lb/gal}$ (0.34 kg/L) of coating as applied (minus water and exempt solvent). Which Months: All Year Statistical Basis: Daily average
- 195 [LAC 33:III.2.123.C.6] Surface coating of assembly line automobiles and light duty trucks. As an alternative to the emission limitation of 2.8 pounds of VOC per gallon of coating applied for the primer surfaer and/or topcoat application, compliance with these limitations may be demonstrated by meeting a standard of: VOC, Total $\leq 15.1 \text{ lb/gal}$ of solids deposited.
- 196 [LAC 33:III.2.123.C.7] Surface coating-magnet wire coating. Coating line: VOC, Total $\leq 1.7 \text{ lb/gal}$ (0.20 kg/L) of coating as applied (minus water and exempt solvent).
- 197 [LAC 33:III.2.123.C.8] Surface coating of metal furniture. Coating line: VOC, Total $\leq 3.0 \text{ lb/gal}$ (0.36 kg/L) of coating (minus water and exempt solvent).
- 198 [LAC 33:III.2.123.C.9.a] Surface coating of miscellaneous metal parts and products. Powder Coating: VOC, Total $\leq 0.4 \text{ lb/gal}$ (0.05 kg/L) of coating as applied (minus water and exempt solvent).
- 199 [LAC 33:III.2.123.C.9.b] Surface coating of miscellaneous metal parts and products. Other: VOC, Total $\leq 3.0 \text{ lb/gal}$ (0.36 kg/L) of coating as applied (minus water and exempt solvent). These limits do not apply to operations covered in LAC 33:III.2123.C.1-8 or 11 or exterior coating of fully assembled aircraft, auto refinishing, and auto customizing topcoating (processing less than 35 vehicles per day).
- 200 [LAC 33:III.2.123.C.9] Surface coating of miscellaneous metal parts and products. Air or Force Air Dried Items (not oven dried) Coating: VOC, Total $\leq 3.5 \text{ lb/gal}$ (0.42 kg/L) of coating as applied (minus water and exempt solvent).
- 201 [LAC 33:III.2.123.C.9] Surface coating of miscellaneous metal parts and products. Clear Coat Coating: VOC, Total $\leq 4.3 \text{ lb/gal}$ (0.52 kg/L) of coating as applied (minus water and exempt solvent).
- 202 [LAC 33:III.2.123.C.9] Surface coating of miscellaneous metal parts and products. Outdoor or Harsh Exposure or Extreme Performance Characteristics Coating: VOC, Total $\leq 3.5 \text{ lb/gal}$ (0.42 kg/L) of coating as applied (minus water and exempt solvent).
- 203 [LAC 33:III.2.123.C.9] Surface coating of miscellaneous metal parts and products. Frequent color changes and/or large numbers of colors applied, or first coat on untreated ferrous substrate: VOC, Total $\leq 3.0 \text{ lb/gal}$ (0.36 kg/L) of coating as applied (minus water and exempt solvent).
- 204 [LAC 33:III.2.123.D.1] Which Months: All Year Statistical Basis: Daily average VOC, Total $\geq 80\%$ control efficiency.
- 205 [LAC 33:III.2.123.D.1] Which Months: All Year Statistical Basis: None specified Submit design data for each capture system and emission control device that is proposed for use to the Office of Environmental Services for approval.

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0001 Surface Coating****ARE 0002 - Surface Coating Subject to LAC 33:III.2123**

- 206 [LAC 33:III.2123.D.1] Determine the effectiveness of the capture system (i.e. capture efficiency) using the procedure specified in LAC 33:III.2123.E.6.
Determine compliance by the procedure specified in "Control of Volatile Organic Emissions for Existing Stationary Sources. Vol. 2-Surface Coating of Cans, Coils, Paper, Fabric, Autos and Lt. Duty Trucks", (EPA 450/2-77-008), the procedures specified in "Measurement of Volatile Organic Compounds" (EPA-450/2-78-041), a method approved by DEQ or certification from the paint manufacturer concerning the solvent makeup of the paint. Treat exempt solvents the same as water in calculating the VOC content per gallon of coating.
Determine compliance with LAC 33:III.2123.C.6 in accordance with EPA's "Protocol for Determining the Daily Volatile Organic Compound Emission Rate of Automobile and Light Duty Truck Topcoat Operations", EPA 450/3-88-018, December, 1988.
- 208 [LAC 33:III.2123.D.4] Test the improved transfer efficiency equipment following procedures approved in advance by DEQ and consistent with those transfer efficiency testing procedures specified in LAC 33:III.2123.E.5. Calculate the applicable emission limit using the transfer efficiency baseline established by DEQ and determine compliance following a calculation procedure also approved by DEQ.
- 209 [LAC 33:III.2123.D.9] Determine compliance with LAC 33:III.2123.A, C, and D by applying the test methods specified in LAC 33:III.2123.E.1 through E.6, as appropriate.
- 210 [LAC 33:III.2123.E] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in LAC 33:III.2123.F.1 through F.4 to verify compliance with LAC 33:III.2123. Maintain records for at least two years.
- 211 [LAC 33:III.2123.F] Comply with the requirements of LAC 33:III.2123 as soon as practicable, but in no event later than one year from the promulgation of the regulation revision, if subject to LAC 33:III.2123 as a result of a revision of LAC 33:III.2123.

ARE 0003 - Surface Coating Exempt from LAC 33:III.2123

- 213 [LAC 33:III.2123.F] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in LAC 33:III.2123.F.1 through F.4 to verify exemption from LAC 33:III.2123. Maintain records for at least two years.

ARE 0004 - Miscellaneous Surface Coating Subject to NESHAP HHHHHH

- 214 [40 CFR 63.11173(e)(1)] Ensure that all painters are certified that they have completed training in the proper spray application of surface coatings and the proper setup and maintenance of spray equipment, as specified in 40 CFR 63.11173(f). Subpart HHHHHH. [40 CFR 63.11173(e)(1)]
Ensure that all spray booths, preparation stations, and mobile enclosures are fitted with a type of filter technology that is demonstrated to achieve at least 98% capture of paint overspray. Subpart HHHHHH. [40 CFR 63.11173(e)(2)(1)]
Ensure that spray booths and preparation stations that are used to coat miscellaneous parts and products or vehicle subassemblies have a full roof, at least three complete walls or complete side curtains, and must be ventilated so that air is drawn into the booth. Subpart HHHHHH. [40 CFR 63.11173(e)(2)(iii)]
Apply all spray-applied coatings with a high volume, low pressure (HVLP) spray gun, electrostatic application, airless spray gun, air-assisted airless spray gun, or an equivalent technology that is demonstrated by the spray gun manufacturer to achieve transfer efficiency comparable to one of the spray gun technologies listed above for a comparable operation, and for which written approval has been obtained from DEQ. Subpart HHHHHH. [40 CFR 63.11173(e)(3)]

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0001 Surface Coating**ARE 0004 - Miscellaneous Surface Coating Subject to NESHAP HHHHHH**

- Conduct all paint spray gun cleaning so that an atomized mist or spray of gun cleaning solvent and paint residue is not created outside of a container that collects used gun cleaning solvent. Subpart HHHHHHH. [40 CFR 63.11173(e)(4)]
- Submit Notification of Changes Report: Due annually prior to March 1, if information previously submitted in either the initial notification required by 40 CFR 63.11175(a), Notification of Compliance, or a previous annual notification of changes report submitted under 40 CFR 63.11176(a), has changed. Include the information specified in 40 CFR 63.11176(a)(1) and (a)(2). Subpart HHHHHHH. [40 CFR 63.11176(a)]
- Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11177(a) through (d) and (g) and (h). Subpart HHHHHHH.
- Maintain copies of the records specified in 40 CFR 63.11177 for a period of at least five years after the date of each record. Keep copies of records on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date. After the two year period records may be kept off-site. Subpart HHHHHHH.
- All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A as delineated in Table 1 of 40 CFR 63 Subpart HHHHHHH.

ARE 0005 - Motor Vehicle and Mobile Equipment Surface Coating Subject to NESHAP HHHHHH

- Ensure that all painters are certified that they have completed training in the proper spray application of surface coatings and the proper setup and maintenance of spray equipment, as specified in 40 CFR 63.11173(f). Subpart HHHHHHH. [40 CFR 63.11173(e)(1)]
- Ensure that all spray booths, preparation stations, and mobile enclosures are fitted with a type of filter technology that is demonstrated to achieve at least 98% capture of paint overspray. Subpart HHHHHHH. [40 CFR 63.11173(e)(2)(i)]
- Ensure that spray booths and preparation stations used to refinish complete motor vehicles or mobile equipment are fully enclosed with a full roof, and four complete walls or complete side curtains, and are ventilated at negative pressure so that air is drawn into any openings in the booth walls or preparation station curtains. If a spray booth is fully enclosed and has seals on all doors and other openings and has an automatic pressure balancing system, it may be operated at up to, but not more than, 0.05 inches water gauge positive pressure. Subpart HHHHHHH. [40 CFR 63.11173(e)(2)(ii)]
- Ensure that mobile ventilated enclosures that are used to perform spot repairs enclose and, if necessary, seal against the surface around the area being coated such that paint overspray is retained within the enclosure and directed to a filter to capture paint overspray. Subpart HHHHHHH. [40 CFR 63.11173(e)(2)(iv)]
- Apply all spray-applied coatings with a high volume, low pressure (HVL/P) spray gun, electrostatic application, airless spray gun, air-assisted airless spray gun, or an equivalent technology that is demonstrated by the spray gun manufacturer to achieve transfer efficiency comparable to one of the spray gun technologies listed above for a comparable operation, and for which written approval has been obtained from DEQ. Subpart HHHHHHH. [40 CFR 63.11173(e)(3)]
- Conduct all paint spray gun cleaning so that an atomized mist or spray of gun cleaning solvent and paint residue is not created outside of a container that collects used gun cleaning solvent. Subpart HHHHHHH. [40 CFR 63.11173(e)(4)]

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER2090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0001 Surface Coating**ARE 0005 - Motor Vehicle and Mobile Equipment Surface Coating Subject to NESHAP HHHHHH**

- 229 [40 CFR 63.11176(a)] Submit Notification of Changes Report: Due annually prior to March 1, if information previously submitted in either the initial notification required by 40 CFR 63.11175(a), Notification of Compliance, or a previous annual notification of changes report submitted under 40 CFR 63.11176(a), has changed. Include the information specified in 40 CFR 63.11176(a)(1) and (a)(2). Subpart HHHHHH. [40 CFR 63.11176(a)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11177(a) through (d) and (g) and (h). Subpart HHHHHH.
- Maintain copies of the records specified in 40 CFR 63.11177 for a period of at least five years after the date of each record. Keep copies of records on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date. After the two year period records may be kept off-site. Subpart HHHHHH.
- All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A as delineated in Table 1 of 40 CFR 63 Subpart HHHHHH.

ARE 0006 - Surface Coating Subject to NESHAP XXXXXX

- 233 [40 CFR 63.11516(d)(1)(i)] Ensure that spray booths or spray rooms have a full roof, at least two complete walls, and one or two complete side curtains or other barrier material so that all four sides are covered. Ventilate the spray booths or spray rooms so that air is drawn into the booth and leaves only through the filter. The roof may contain narrow slots for connecting fabricated products to overhead cranes, and/or for cords or cables. Subpart XXXXXX. [40 CFR 63.11516(d)(1)(i)]
- Fit all spray booths or spray rooms with a type of filter technology that is demonstrated to achieve at least 98 percent capture of MFHAP. Subpart XXXXXX. [40 CFR 63.11516(d)(1)(ii)]
- Perform regular inspection and replacement of the filters in all spray booths or spray rooms according to manufacturer's instructions. Subpart XXXXXX. [40 CFR 63.11516(d)(1)(iii)]
- Equip spray booths or spray rooms with a water curtain that is operated and maintained according to the manufacturer's specifications and that achieves at least 98 percent control of MFHAP. Subpart XXXXXX. [40 CFR 63.11516(d)(1)(iv)]
- Apply all paints applied via spray-applied painting with a high-volume, low-pressure (HVLP) spray gun, electrostatic application, airless spray gun, air-assisted airless spray gun, or an equivalent technology that is demonstrated to achieve transfer efficiency comparable to one of these spray gun technologies for a comparable operation, and for which written approval has been obtained from DEQ. Subpart XXXXXX. [40 CFR 63.11516(d)(2)]
- Perform all cleaning of paint spray guns with either non-HAP gun cleaning solvents, or in such a manner that an atomized mist of spray of gun cleaning solvent and paint residue is not created outside of a container that collects the used gun cleaning solvent. Subpart XXXXXX. [40 CFR 63.11516(d)(4)]
- Ensure that all workers performing painting are certified that they have completed training in the proper spray application of paints and the proper setup and maintenance of spray equipment. The spray application of paint is prohibited by persons who are not certified as having completed the training described in 40 CFR 63.11516(d)(6). Subpart XXXXXX. [40 CFR 63.11516(d)(5)]

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0001 Surface Coating**ARE 0006 - Surface Coating Subject to NESHAP XXXXX**

- 240 [40 CFR 63.11516(d)(6)] Ensure and certify that all new and existing personnel, including contract personnel, who spray apply paints are trained in the proper application of paints as required by 40 CFR 63.11516(d)(5). Ensure that the training program includes, at a minimum, the items listed in 40 CFR 63.11516(d)(6)(i) through (d)(6)(iii). Subpart XXXXXX. [40 CFR 63.11516(d)(6)]
- 241 [40 CFR 63.11516(d)(9)] Ensure that all personnel receive refresher training that meets the requirements of 40 CFR 63.11516 and are re-certified every 5 years. Subpart XXXXXX. [40 CFR 63.11516(d)(9)]
- 242 [40 CFR 63.11519(b)(1)] Submit Certification and Compliance Report: Due annually, by the 31st of January. Include the information specified in 40 CFR 63.11519(b)(4) through (b)(9), as applicable. Keep the report in a readily-accessible location for inspector review. Submit exceedance report with the certification and compliance report if an exceedance has occurred during the year. Subpart XXXXXX. [40 CFR 63.11519(b)(1)]
- 243 [40 CFR 63.11519(e)(15)] Keep records in a form suitable and readily available for expeditions review, according to 40 CFR 63.10(b)(1). Keep each record for 5 years following the date of each occurrence, measurement, corrective action, report, or record. Keep each record on-site for at least 2 years after the date of each occurrence, measurement, corrective action, report, or record according to 40 CFR 63.10(b)(1). The remaining 3 years may be kept off-site. Subpart XXXXXX. [40 CFR 63.11519(e)(15)]
- 244 [40 CFR 63.11519(c)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]
- 245 [40 CFR 63.11519(c)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]
- 246 [40 CFR 63.] All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A as delineated in Table 4 of 40 CFR 63 Subpart XXXXXX.

Group: PCS 0003 Welding, Cutting, Grinding, Machining, and Polishing

Group Members: EQT 0001 EQT 0002 EQT 0003

EQT 0001 - All Welding, Cutting, Grinding, Machining, and Polishing

- 247 [LAC 33:III.1305] Prevent particulate matter from becoming airborne by taking all reasonable precautions. These precautions shall include, but not be limited to, those specified in LAC 33:III.1305.A.1-7.
- 248 [LAC 33:III.1311.C] Opacity <= 20 percent; except emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes.
- Which Months: All Year Statistical Basis: Six-minute average

EQT 0002 - Welding Subject to NESHAP XXXXX

- 249 [40 CFR 63.11516(f)(1)] Operate all equipment, capture, and control devices associated with welding operations according to manufacturer's instructions. Subpart XXXXXX. [40 CFR 63.11516(f)(1)]

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**Group: PCS 0003 Welding, Cutting, Grinding, Machining, and Polishing****EQT 0002 - Welding Subject to NESHAP XXXXXX**

- 250 [40 CFR 63.11516(f)(2)] Implement one or more of the management practices specified in 40 CFR 63.11516(f)(2)(i) through (f)(2)(v) to minimize emissions of MFHAP, as practicable, while maintaining the required welding quality through the application of sound engineering judgment. Subpart XXXXXX. [40 CFR 63.11516(f)(2)]
- 251 [40 CFR 63.11516(f)(3)] Visible emissions monitored by 40 CFR 60, Appendix A, Method 22 daily on each day the process is in operation, during the operation of the process. Subpart XXXXXX. [40 CFR 63.11516(f)(3), 40 CFR 63.11517(b)(1)]
- Which Months: All Year Statistical Basis: None specified
- Visible emissions monitored by 40 CFR 60, Appendix A, Method 22 monthly, if no visible fugitive emissions are detected in four consecutive weekly EPA Method 22 tests performed in accordance with 40 CFR 63.11517(b)(2). Resume weekly EPA Method 22 tests in accordance with 40 CFR 63.11517(b)(2) if visible fugitive emissions are detected during these tests. Subpart XXXXXX. [40 CFR 63.11516(f)(3), 40 CFR 63.11517(b)(3)]
- Which Months: All Year Statistical Basis: None specified
- Visible emissions monitored by 40 CFR 60, Appendix A, Method 22 weekly, if no visible fugitive emissions are detected in consecutive daily EPA Method 22 test, performed in accordance with 40 CFR 63.11517(b)(1) for 10 days of work day operation of the process. Resume EPA Method 22 testing of that operation once per day during each day that the process is in operation, in accordance with 40 CFR 63.11517(b)(1), if visible fugitive emissions are detected during these tests. Subpart XXXXXX. [40 CFR 63.11516(f)(3), 40 CFR 63.11517(b)(2)]
- Which Months: All Year Statistical Basis: None specified
- Visible emissions monitored by 40 CFR 60, Appendix A, Method 22 quarterly, if no visible fugitive emissions are detected in three consecutive monthly EPA Method 22 tests performed in accordance with 40 CFR 63.11517(b)(3). Resume monthly EPA Method 22 tests in accordance with 40 CFR 63.11517(b)(3) if visible fugitive emissions are detected during these tests. Subpart XXXXXX. [40 CFR 63.11516(f)(3), 40 CFR 63.11517(b)(3)]
- Which Months: All Year Statistical Basis: None specified
- Perform corrective actions that include, but are not limited to, inspection of welding fume sources, and evaluation of the proper operation and effectiveness of the management practices or fume control measures implemented in accordance with 40 CFR 63.11516(f)(2), if visible fugitive emissions are detected during any visual determination required in 40 CFR 63.11516(f)(3). Perform a follow-up inspection for visible fugitive emissions in accordance with 40 CFR 63.11517(a) at the primary vent, stack, exit, or opening from the building containing the welding operations after completing corrective actions. Subpart XXXXXX. [40 CFR 63.11516(f)(4)(i)]
- Opacity monitored by 40 CFR 60, Appendix A, Method 9 within 24 hours of the end of the visual determination of fugitive emissions in which visible fugitive emissions were detected, if visible fugitive emissions are detected more than once during any consecutive 12 month period. Monitor opacity at the primary vent, stack, exit, or opening from the building containing the welding operations. Subpart XXXXXX. [40 CFR 63.11516(f)(5)(i), 40 CFR 63.11517(c)]
- Which Months: All Year Statistical Basis: None specified
- Opacity monitored by 40 CFR 60, Appendix A, Method 9 daily during each day that the process is in operation. Subpart XXXXXX. [40 CFR 63.11516(f)(5)(ii), 40 CFR 63.11517(d)(1)]
- Which Months: All Year Statistical Basis: Six-minute average

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities
 Activity Number: PER20090001
 Permit Number: Surface Coating/Fabrication General Master Permit
 Air - Minor Source/Small Source Initial

Group: PCS 0003 Welding, Cutting, Grinding, Machining, and Polishing**EQT 0002 - Welding Subject to NESHAP XXXXXX**

258 [40 CFR 63.11516(f)(5)(ii)] Opacity monitored by 40 CFR 60, Appendix A, Method 9 monthly (once per every 21 days of operation of the process), if the average of the six minute opacities recorded during any of the consecutive weekly EPA Method 9 tests performed in accordance with 40 CFR 63.11517(d)(2) does not exceed 20 percent for four consecutive weekly tests. Resume testing every five days of operation of the process according to the requirements of 40 CFR 63.11517(d)(2) if visible emissions opacity greater than 20 percent is detected during any monthly test. Subpart XXXXXX. [40 CFR 63.11516(f)(5)(ii), 40 CFR 63.11517(d)(3)]

Which Months: All Year Statistical Basis: Six-minute average

259 [40 CFR 63.11516(f)(5)(ii)] Opacity monitored by 40 CFR 60, Appendix A, Method 9 weekly (once per five days of consecutive work day operation), if the average of the six minute opacities recorded during any of the daily consecutive EPA Method 9 tests performed in accordance with 40 CFR 63.11517(d)(1) does not exceed 20 percent for 10 days of operation of the process. Resume testing every day of operation of the process according to the requirements of 40 CFR 63.11517(d)(1) if opacity greater than 20 percent is detected during any of these tests. Subpart XXXXX. [40 CFR 63.11516(f)(5)(ii), 40 CFR 63.11517(d)(2)]

Which Months: All Year Statistical Basis: Six-minute average

260 [40 CFR 63.11516(f)(5)(ii)] Opacity monitored by 40 CFR 60, Appendix A, Method 9 quarterly (once per every 120 days of operation of the process), if the average of the six minute opacities recorded during any of the consecutive monthly EPA Method 9 tests performed in accordance with 40 CFR 63.11517(d)(3) does not exceed 20 percent for three consecutive monthly tests. Resume testing every 21 days (month) of operation of the process according to the requirements of 40 CFR 63.11517(d)(3) if visible emissions opacity greater than 20 percent is detected during any quarterly test. Subpart XXXXXX. [40 CFR 63.11516(f)(5)(ii), 40 CFR 63.11517(d)(4)]

Which Months: All Year Statistical Basis: Six-minute average

261 [40 CFR 63.11516(f)(6)] Perform corrective actions, including inspection of all welding fume sources, and evaluation of the proper operation and effectiveness of the management practices or fume control measures implemented in accordance with 40 CFR 63.11516(f)(2), for each visual determination of emissions opacity performed in accordance with 40 CFR 63.11516(f)(5) for which the average of the six-minute average opacities recorded is 20 percent or less but greater than zero. Subpart XXXXXX. [40 CFR 63.11516(f)(6)] Prepare and implement a Site-Specific Welding Emissions Management Plan, as specified in 40 CFR 63.11516(h)(8), within 30 days of a visual determination of emissions opacity performed in accordance with 40 CFR 63.11516(f)(5) for which the average of the six- minute average opacities recorded exceeds 20 percent. Include the information specified in 40 CFR 63.11516(f)(8)(i)(A) through (f)(8)(i)(F). If a Site-Specific Welding Emissions Management Plan has already been prepared, prepare and implement a revised Site-Specific Welding Emissions Management Plan. During the preparation (or revision) of the Site-Specific Welding Emissions Management Plan, continue to perform visual determinations of emissions opacity, beginning on a daily schedule as specified in 40 CFR 63.11517(d), at the primary vent, stack, exit, or opening from the building containing the welding operations. Subpart XXXXXX. [40 CFR 63.11516(f)(7)] Update the Site-Specific Welding Emissions Management Plan annually to contain current information, as required by 40 CFR 63.11516(f)(8)(i)(C), and submit with the annual certification and compliance report. Subpart XXXXXX. [40 CFR 63.11516(f)(8)(ii)]

263 [40 CFR 63.11516(f)(8)(ii)] Submit Certification and Compliance Report: Due annually, by the 31st of January. Include the information specified in 40 CFR 63.11519(b)(4) through (b)(9), as applicable. Keep the report in a readily-accessible location for inspector review. Submit exceedance report with the certification and compliance report if an exceedance has occurred during the year. Subpart XXXXXX. [40 CFR 63.11519(b)(1)]

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER2090001

Permit Number: Surface Coating/Fabrication General Master Permit

Air - Minor Source/Small Source Initial

Group: PCS 0003 Welding, Cutting, Grinding, Machining, and Polishing**EQT 0002 - Welding Subject to NESHAP XXXXXX**

- 265 [40 CFR 63.11519(c)(15)] Keep records in a form suitable and readily available for expeditious review, according to 40 CFR 63.10(b)(1). Keep each record for 5 years following the date of each occurrence, measurement, corrective action, report, or record. Keep each record on-site for at least 2 years after the date of each occurrence, measurement, corrective action, report, or record according to 40 CFR 63.10(b)(1). The remaining 3 years may be kept off-site. Subpart XXXXXX. [40 CFR 63.11519(c)(15)]
- 266 [40 CFR 63.11519(c)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]
- 267 [40 CFR 63.11519(c)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]
- 268 [40 CFR 63.] All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A as delineated in Table 4 of 40 CFR 63 Subpart XXXXXX.

EQT 0003 - Dry Grinding, Polishing, and Machining Subject to NESHAP XXXXXX

- 269 [40 CFR 63.11516(b)(1)] Take measures necessary to minimize excess dust in the surrounding area to reduce MFHAP emissions, as practicable. Subpart XXXXXX. [40 CFR 63.11516(b)(1)]
- 270 [40 CFR 63.11516(b)(2)] Operate all equipment associated with machining according to manufacturer's instructions. Subpart XXXXXX. [40 CFR 63.11516(b)(2)]
- 271 [40 CFR 63.11516(c)(1)] Capture emissions and vent them to a filtration control device. Subpart XXXXXX. [40 CFR 63.11516(c)(1)]
- 272 [40 CFR 63.11516(c)(2)(i)] Take measures necessary to minimize excess dust in the surrounding area to reduce MFHAP emissions, as practicable. Subpart XXXXXX. [40 CFR 63.11516(c)(2)(i)]
- 273 [40 CFR 63.11516(c)(2)(ii)] Operate all equipment associated with the operation of dry grinding and dry polishing with machines, including the filtration control device, according to manufacturer's instructions. Subpart XXXXXX. [40 CFR 63.11516(c)(2)(ii)]
- 274 [40 CFR 63.11519(b)(1)] Submit Certification and Compliance Report: Due annually, by the 31st of January. Include the information specified in 40 CFR 63.11519(b)(4) through (b)(9), as applicable. Keep the report in a readily-accessible location for inspector review. Submit exceedance report with the certification and compliance report if an exceedance has occurred during the year. Subpart XXXXXX. [40 CFR 63.11519(b)(1)]
- 275 [40 CFR 63.11519(c)(15)] Keep records in a form suitable and readily available for expeditious review, according to 40 CFR 63.10(b)(1). Keep each record for 5 years following the date of each occurrence, measurement, corrective action, report, or record. Keep each record on-site for at least 2 years after the date of each occurrence, measurement, corrective action, report, or record according to 40 CFR 63.10(b)(1). The remaining 3 years may be kept off-site. Subpart XXXXXX. [40 CFR 63.11519(c)(15)]
- 276 [40 CFR 63.11519(c)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]
- 277 [40 CFR 63.11519(c)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.11519(c)(1) through (c)(14), as applicable. Subpart XXXXXX. [40 CFR 63.11519(c)]
- 278 [40 CFR 63.] All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A as delineated in Table 4 of 40 CFR 63 Subpart XXXXXX.

SPECIFIC REQUIREMENTS

AIID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities

Activity Number: PER20090001

Permit Number: Surface Coating/Fabrication General Master Permit
Air - Minor Source/Small Source Initial**ARE 0011 - Unpaved Roads**

279 [LAC 33:III.1305]

Prevent particulate matter from becoming airborne by taking all reasonable precautions. These precautions shall include, but not be limited to, those specified in LAC 33:III.1305.A.1-7.

EQT 0004 - Dryers and Heaters

280 [LAC 33:III.1101.B]

Opacity <= 20 percent, except during the cleaning of a fire box or building of a new fire, soot blowing or lancing, charging of an incinerator, equipment changes, ash removal or rapping of precipitators, which may have an opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes (Complies by using sweet natural gas as fuel).

Which Months: All Year Statistical Basis: None specified

Total suspended particulate <= 0.6 lb/MMBTU of heat input (Complies by using sweet natural gas as fuel).

Which Months: All Year Statistical Basis: None specified

EQT 0009 - Storage Vessels Storing VOC >1.5 psia, >250 gallons, and <10,000 gallons

282 [LAC 33:III.2103.A]

Equip with a submerged fill pipe.

EQT 0010 - Dust Filters

283 [LAC 33:III.501.C.6]

Particulate matter (10 microns or less) >= 99 % removal efficiency from filter manufacturer's certification.

Which Months: All Year Statistical Basis: None specified

Filter vents: Visible emissions recordkeeping by electronic or hard copy daily. Keep records of visible emission checks on site and available for inspection by the Office of Environmental Compliance, Surveillance Division.

Filter vents: Visible emissions monitored by visual inspection/determination daily. If visible emissions are observed, restore operation of the filter to its normal or usual manner of operation as expeditiously as practicable, but at a minimum within three working days, in accordance with good air pollution control practices for minimizing emissions.

Which Months: All Year Statistical Basis: None specified

EQT 0011 - Carbon Adsorption

286 [LAC 33:III.501.C.6]

287 [LAC 33:III.501.C.6]

Replace canisters as necessary to maintain a control efficiency of 95% minimum. Equipment/operational data recordkeeping by electronic or hard copy upon each occurrence of breakthrough. Keep records of the number of breakthroughs on site and available for inspection by the Office of Environmental Compliance, Surveillance Division.

Cease using equipment when breakthrough occurs and do not resume use until the carbon adsorption unit has been regenerated or replaced. VOC, Total monitored by the regulation's specified method(s) daily. Monitor VOC breakthrough using a portable VOC detector until the reliable life expectancy of the canister is established.

Which Months: All Year Statistical Basis: None specified

Equipment/operational data recordkeeping by electronic or hard copy daily. Keep records of the tests to determine carbon canister life, as well as the dates of canister replacement, on site and available for inspection by the Office of Environmental Compliance, Surveillance Division.

SPECIFIC REQUIREMENTS

AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities
 Activity Number: PER20090001
 Permit Number: Surface Coating/Fabrication General Master Permit
 Air - Minor Source/Small Source Initial

EQT 0011 - Carbon Adsorption

- 291 [LAC 33:III.501.C.6]
 292 [LAC 33:III.501.C.6]

Utilize a monitoring system approved by the Environmental Technology Division, Engineering Services.
 Control VOC emissions using activated carbon adsorption units (at 75% efficiency) that have been approved by the Environmental Technology Division, Engineering Services.

EQT 0012 - Thermal Oxidizer

- 293 [LAC 33:III.1101.B]

Opacity <= 20 percent, except during the cleaning of a fire box or building of a new fire, soot blowing or lancing, changing of an incinerator, equipment changes, ash removal or rapping of precipitators, which may have an opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes (Complies by using sweet natural gas as fuel).
 Which Months: All Year Statistical Basis: None specified
 Opacity <= 20 percent; except emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes (Complies by using sweet natural gas as fuel).
 Which Months: All Year Statistical Basis: Six-minute average

UNF 0001 - Entire Facility

- 295 [LAC 33:III.1103]

Emissions of smoke which pass onto or across a public road and create a traffic hazard by impairment of visibility as defined in LAC 33:III.111 or intensify an existing traffic hazard condition are prohibited.
 Outdoor burning of waste material or other combustible material is prohibited.
 Emissions of particulate matter which pass onto or across a public road and create a traffic hazard by impairment of visibility or intensify an existing traffic hazard condition are prohibited.
 Maintain best practical housekeeping and maintenance practices at the highest possible standards to reduce the quantity of organic compounds emissions. Good housekeeping shall include, but not be limited to, the practices listed in LAC 33:III.2113.A.1-5.
 Failure to pay the prescribed application fee or annual fee as provided herein, within 90 days after the due date, will constitute a violation of these regulations and shall subject the person to applicable enforcement actions under the Louisiana Environmental Quality Act including, but not limited to, revocation or suspension of the applicable permit, license, registration, or variance.
 VOC, Total: Attainment parishes: VOC, Total < 90 tons/yr.
 Nitrogen oxides: Attainment parishes: NOx < 90 tons/yr.
 VOC, Total: Nonattainment parishes: VOC, Total < 20 tons/yr.
 Any Individual Toxic Air Pollutant (TAP) emitted shall not exceed the lb/hr and tons/yr limits of Table 1. Facilities which emit a TAP not listed in Table 1 shall not exceed the minimum emission rate (MER) for that TAP listed in Table 51.1 and 51.2 of LAC 33:III.Chapter 51. No individual TAP shall exceed eight (8) tons per year.
 Nitrogen oxides: Nonattainment parishes: NOx < 20 tons/yr.
 Particulate matter (10 microns or less): PM10 < 15 tons/yr.
 Carbon monoxide: CO < 90 tons/yr.

SPECIFIC REQUIREMENTS**AI ID: 163497 - Minor Source Air General Permit for Surface Coating and Fabrication Facilities****Activity Number: PER20090001****Permit Number: Surface Coating/Fabrication General Master Permit****Air - Minor Source/Small Source Initial****UNF 0001 - Entire Facility**

307 [LAC 33.III.501.C.6]

308 [LAC 33.III.501.C.6]

Sulfur dioxide: SO₂ < 40 tons/yr.

Equipment/operational data recordkeeping by electronic or hard copy monthly: Permittee shall maintain records demonstrating compliance with Section III of this general permit for any consecutive twelve (12) months. Keep records on site for a minimum of two (2) years and available for review by DEQ personnel upon request. Noncompliance with an applicable limitation is a reportable violation of the permit. Notify the Office of Environmental Compliance, Enforcement Division if any emissions exceed the applicable maximum listed in Section III of this general permit for any twelve (12) consecutive months.

309 [LAC 33.III.5611.A] Submit standby plan for the reduction or elimination of emissions during an Air Pollution Alert, Air Pollution Warning, or Air Pollution Emergency: Due within 30 days after requested by the administrative authority.

310 [LAC 33.III.5611.B] During an Air Pollution Alert, Air Pollution Warning or Air Pollution Emergency, make the standby plan available on the premises to any person authorized by the department to enforce these regulations.

311 [LAC 33.III.919.D] Submit Emission Inventory (EI)/Annual Emissions Statement: Due annually, by the 31st of March (unless an alternate date has been established by LDEQ) for the period January 1 to December 31 of the previous year when required by Section V of this general permit. Submit emission inventory data in the format specified by the Office of Environmental Assessment. Include all data applicable to the emissions source(s), as specified in LAC 33.III.919.A-D.